

Package: UKFE (via r-universe)

September 11, 2024

Type Package

Title UK Flood Estimation

Version 0.3.6

Maintainer Anthony Hammond <agqhammond@gmail.com>

Description Functions to implement the methods of the Flood Estimation Handbook (FEH), associated updates and the revitalised flood hydrograph model (ReFH). Currently the package uses NRFA peak flow dataset version 13. Aside from FEH functionality, further hydrological functions are available. Most of the methods implemented in this package are described in one or more of the following: ``Flood Estimation Handbook'', Centre for Ecology & Hydrology (1999, ISBN:0 948540 94 X). ``Flood Estimation Handbook Supplementary Report No. 1'', Kjeldsen (2007, ISBN:0 903741 15 7). ``Regional Frequency Analysis - an approach based on L-moments'', Hosking & Wallis (1997, ISBN: 978 0 521 01940 8). ``Proposal of the extreme rank plot for extreme value analysis: with an emphasis on flood frequency studies'', Hammond (2019, <doi:10.2166/nh.2019.157>). ``Making better use of local data in flood frequency estimation'', Environment Agency (2017, ISBN: 978 1 84911 387 8). ``Sampling uncertainty of UK design flood estimation'', Hammond (2021, <doi:10.2166/nh.2021.059>). ``Improving the FEH statistical procedures for flood frequency estimation'', Environment Agency (2008, ISBN: 978 1 84432 920 5). ``Low flow estimation in the United Kingdom'', Institute of Hydrology (1992, ISBN 0 948540 45 1). Wallingford HydroSolutions, (2016, <<http://software.hydrosolutions.co.uk/winfap4/Urban-Adjustment-Procedure-Technical-Note.pdf>>). Data from the UK National River Flow Archive (<<https://nrfa.ceh.ac.uk/>>, terms and conditions: <<https://nrfa.ceh.ac.uk/costs-terms-and-conditions>>).

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2
Depends R (>= 3.5.0)
Imports xml2, methods
NeedsCompilation no
Author Anthony Hammond [aut, cre]
Date/Publication 2024-09-10 21:40:02 UTC
Repository <https://agqhammond.r-universe.dev>
RemoteUrl <https://github.com/cran/UKFE>
RemoteRef HEAD
RemoteSha c053b20a8fac38521b50e2c57170288f35849e1e

Contents

AddGauge	4
AggDayHour	5
AMextract	6
AMImport	8
AMplot	8
AMSP	9
ARF	10
BFI	11
CDsXML	12
DDF	13
DDF99	14
DDF99Pars	15
DDFImport	16
DesHydro	17
DeTrend	18
DiagPlots	19
DonAdj	20
EncProb	21
ERPlot	22
EVPlot	23
EVPlotAdd	24
EVPool	26
GenLogAM	27
GenLogEst	28
GenLogGF	29
GenLogPars	30
GenParetoEst	31
GenParetoGF	32
GenParetoPars	33
GenParetoPOT	34
GetAM	35
GetCDs	36

GetMetOffice	36
GetNRFA	37
GetQMED	38
GetRainEA	39
GetRainSEPA	40
GEVAM	41
GEVEst	42
GEVGF	43
GEVPars	44
GoFCompare	45
GoFComparePool	46
GumbelAM	47
GumbelEst	48
GumbelGF	49
GumbelPars	49
H2	50
HydroPlot	51
Kappa3AM	53
Kappa3Est	54
Kappa3GF	55
Kappa3Pars	56
Lcv	57
LcvUrb	57
LKurt	58
Lmoms	59
LRatioChange	60
LSkew	61
LSkewUrb	62
MonthlyStats	63
NGRDist	64
NonFloodAdj	65
NonFloodAdjPool	66
NRFAData	67
OptimPars	68
Pool	69
PoolEst	70
PoolSmall	72
POTextract	74
POTt	75
QMED	77
QMEDData	78
QMEDDonEq	79
QMEDfseSS	80
QMEDLink	81
QMEDPOT	82
QuickResults	83
Rating	84
ReFH	85

SCF	87
SimData	88
ThamesPQ	89
TrendTest	90
UAF	91
UEF	92
UKOutline	92
Uncertainty	93
UncSS	95
WeightsGLcv	96
WeightsGLSkew	96
WeightsUnLcv	97
WeightsUnLSkew	98
WGaugLcv	99
WGaugLSkew	99
WungLcv	100
WungLSkew	101
Zdists	102

Index	104
--------------	------------

AddGauge	<i>Add an AMAX sample</i>
----------	---------------------------

Description

This function allows the user to add an AMAX sample and associated catchment descriptors for use with the FEH process.

Usage

```
AddGauge(CDs, AMAX, ID)
```

Arguments

CDs	catchment descriptor object imported using the CDXML function.
AMAX	Either a data.frame with date (or POSIXct) in the first column and a numeric vector in the second (the AMAX). Or an AMAX sample (a numeric vector).
ID	This is a user supplied identification number for the AMAX.

Details

The function provides the necessary AMAX sample statistics and data.frame for adding catchment descriptors to the NRFAData data.frame. The user must then add these outputs using the rbind function (see example). The AMAX could be read in or pasted in by the user or imported using the AMImport function. Once they are added they can be used in the current R session. If a new session is started (rather than a saved workspace) the added AMAX would need to be added again.

Value

A list object. The first element is a data.frame which is a row of statistics and descriptors to be added to the NRFAData data.frame. The second element is the AMAX sample formatted to be added to the AMSP data.frame

Author(s)

Anthony Hammond

Examples

```
#Read in AMAX and catchment descriptors
## Not run: AMAdd <- AMImport(r"{D:\NRFAPeakFlow_v12_1_0\suitable-for-neither\027003.am}")
## Not run: CDSAdd <- CDSXML(r"{D:\NRFAPeakFlow_v12_1_0\suitable-for-neither\027003.xml}")

#Apply the function and then add the results to the necessary data.frames.

## Not run: Gauge27003 <- AddGauge(CDSAdd, AMAdd, ID = "27003")
#Add the descriptors and stats (the first element of the output) to the NRFAData data.frame
## Not run: NRFAData <- rbind(NRFAData, Gauge27003[[1]])
#Add the AMAX to the AMSP data.frame.
## Not run: AMSP <- rbind(AMSP, Gauge27003[[2]])
```

AggDayHour

Aggregate a time series

Description

Aggregates time series data, creating hourly data from 15 minute data for example.

Usage

```
AggDayHour(x, func, Freq = "Day", hour = 9)
```

Arguments

x	a data.frame with POSIXct in the first column and numeric vector in the second.
func	the function used for aggregation; mean, max, or sum, for example.
Freq	Choices are "Day", or "Hour".
hour	An integer between 0 and 23. This is used if "Day" is chosen in the Freq argument to determine when the day starts.

Details

The function can be used with a data.frame with POSIXct in the first column and a variable in the second. You can choose the level of aggregation in hours, or you can choose daily. In the daily case you can choose which hour of the day to start the aggregation. For example, you might want mean flows from 09:00 rather than midnight. You can also choose the function used to aggregate the data. For example, you might want "sum" for rainfall, and "mean" for flow. When aggregating hourly the aggregation starts at whatever hour is in the first row of x and the associated time stamps will reflect this.

Value

A data.frame with POSIXct in the first column (unless daily is chosen, then it's Date class), and the aggregated variable in the second column

Author(s)

Anthony Hammond

Examples

```
#Create a data.frame with a normally distributed variable at
#a 15 minute sampling rate.
TS <- seq(as.POSIXct("2000-01-01 00:00:00",
tz = "Europe/London"), as.POSIXct("2001-01-01 00:00:00", tz = "Europe/London"), by = 60*15)
TS <- data.frame(DateTime = TS, Var = rnorm(length(TS), 10, 2))
#use the function to aggregate to an hourly sampling rate, taking the maximum of each hour
Hourly <- AggDayHour(TS, func = max, Freq = "Hour")
#now aggregate with the mean at a daily scale
Daily <- AggDayHour(TS, func = mean, Freq = "Day")
```

AMextract

Annual maximum extraction

Description

Extracts the annual maximum peaks (with other options) from a data.frame which has dates (or POSIXct) in the first column and variable in the second.

Usage

```
AMextract(
  x,
  func = NULL,
  Calendar = FALSE,
  Trunc = TRUE,
  Plot = TRUE,
  Title = "Hydrological annual maximum sequence",
  Ylabel = "Magnitude"
)
```

Arguments

x	a data.frame with dates (or POSIXct) in the first column and variable in the second
func	A user chosen function to extract statistics other than maximums.
Calendar	logical. If FALSE, the hydrological year maximums are returned. If TRUE, the calendar year maximums are returned.
Trunc	logical with a default of TRUE. When true the beginning and end of the data.frame are first truncated so that it starts and ends at the start and end of the hydrological year (or Calendar year if Calendar = TRUE).
Plot	a logical argument with a default of TRUE. If TRUE the extracted annual maximum is plotted
Title	Title of the plot when. Default is "Hydrological annual maximum sequence"
Ylabel	Label for the y axis. Default is "Annual maximum quantiles"

Details

The peaks are extracted based on the UK hydrological year (unless Calendar = TRUE), which starts October 1st and ends September 30th. If Trunc = TRUE, partial years (non-full years from the beginning and end) are removed, otherwise the maximum value may not be the true annual maximum of the year. If there are NAs for full years in the data, an -Inf or NA will be returned for that year. The default is to extract maximums but the user can use the func argument to choose other statistics (mean or sum for example). Note that if the data has a sub-daily resolution, it is first aggregated to a daily resolution (with a 09:00 start) before the extraction. For example, the maximum for each day is extracted, then the annual maximums are extracted.

Value

a data.frame with columns; WaterYear and AM. By default AM is the annual maximum sample, but will be any statistic used as the func argument.

Author(s)

Anthony Hammond

Examples

```
#Extract the Thames AMAX daily mean flow and display the first six rows
ThamesAM <- AMextract(ThamesPQ[,c(1,3)])
head(ThamesAM)
#Extract the annual rainfall totals and change the plot labels accordingly
ThamesAnnualP <- AMextract(ThamesPQ[,1:2], func = sum, Title = "", Ylab = "Rainfall (mm)")
```

AMImport *Import an annual maximum (AMAX) sample from NRFA peak flow .AM files*

Description

Imports the peak flows and dates from from NRFA peak flow .AM files, excluding the rejected years

Usage

```
AMImport(x)
```

Arguments

x the file path for the .AM file

Details

File paths for importing data require forward slashes. On some operating systems, such as windows, the copy and pasted file paths will have backward slashes and would need to be changed accordingly.

Value

A data.frame with columns; Date and Flow

Author(s)

Anthony Hammond

Examples

```
#Import an AMAX sample and display the first six rows in the console
## Not run: AM.4003 <- AMImport("C:/Data/NRFAPeakFlow_v11/Suitable for QMED/4003.AM")
## Not run: head(AM.4003)]
```

AMplot *Plot of the annual maximum sample*

Description

Provides two plots. First, a histogram of the sample, second, a barplot

Usage

```
AMplot(x)
```


Arguments

x a data.frame with at least two columns. The first a date column and the second the annual maximum (AM) sequence. A third column with the station id is necessary for inclusion of the id in the plot title. An AM object derived from the GetAM or ImportAM functions.

Details

When used with a GetAM object or any data.frame with dates in the first column, the barplot is daily. Therefore, although it's an annual maximum (AM) sequence, some bars will be closer together depending on the number of days between them.

Value

a histogram of the AMAX sample and a barplot

Author(s)

Anthony Hammond

Examples

```
#Get an AMAX sample and plot
AMplot(GetAM(58002))
```

AMSP	<i>National River Flow Archive (NRFA) annual maximum data for sites suitable for pooling</i>
------	--

Description

A data.frame with three columns; Date, Flow, id. NRFA Peak Flow Dataset - Version 13.0.2

Usage

```
AMSP
```

Format

A data frame with 26539 rows and 3 columns

Date Date

Flow Annual maximum peak flow, m3/s

id Station identification number

Source

<https://nrfa.ceh.ac.uk/peak-flow-dataset>

ARF

*Areal reduction factor (ARF)***Description**

The results of applying, to a rainfall depth, the ratio of the rainfall over an area to the rainfall depth of the same duration at a representative point in the area.

Usage

ARF(Depth, Area, D)

Arguments

Depth	depth of rainfall
Area	catchment area in km ²
D	duration in hours

Details

The ARF and its use is detailed in the Flood Estimation Handbook (1999), volume 2. The DDF model is calibrated on point rainfall and the areal reduction factor converts it to a catchment rainfall for use with a rainfall runoff model such as ReFH (see details for ReFH function). The ReFH model includes a design rainfall profile for winter and summer but the depth duration frequency (DDF) model is calibrated on annual maximum peaks as opposed to seasonal peaks. A seasonal correction factor (SCF) is necessary to convert the DDF estimate to a seasonal one. The final depth, therefore is; $\text{Depth} = \text{DDF}_{\text{depth}} \times \text{ARF} \times \text{SCF}$.

Value

the rainfall depth or rainfall return period

Author(s)

Anthony Hammond

Examples

#Derive the ARF for a depth of 30, an area of 500km² and a duration of 12 hours
ARF(30, 500, 12)

BFI	<i>Baseflow index (BFI)</i>
-----	-----------------------------

Description

Calculates the baseflow index from a daily mean flow series

Usage

```
BFI(Q, x.lim = NULL, y.lim = NULL, PlotTitle = "Baseflow plot", Plot = TRUE)
```

Arguments

Q	the daily mean flow series. Numeric vector
x.lim	the x axis limits of the plot. Numeric vector of length two Default is the extents of the data
y.lim	the y axis limits of the plot. Numeric vector of length two. Default is the extents of the data
PlotTitle	the title of the plot. The default is "Baseflow plot"
Plot	a logical argument with a default of TRUE. If TRUE the daily flow is plotted with the baseflow highlighted.

Details

The baseflow index is calculated using the method outlined in Gustard, A. Bullock, A. Dixon, J. M. (1992). Low flow estimation in the United Kingdom. Wallingford, Institute of Hydrology, 88pp. (IH Report No.108)

Value

the baseflow index and if Plot equals TRUE, a plot showing the flow time series (black) and the associated baseflow (red)

Author(s)

Anthony Hammond

Examples

```
# Calculate the BFI from daily discharge at Kingston upon Thames;  
# which is in column three of the ThamesPQ data  
BFI(ThamesPQ[,3])
```

CDsXML

Import catchment descriptors from .xml files

Description

Imports catchment descriptors from xml files either from an FEH webservice download or from the Peakflows dataset downloaded from the national river flow archive (NRFA) website

Usage

CDsXML(x)

Arguments

x the xml file path

Details

File paths for importing data require forward slashes. On some operating systems, such as windows, the copy and pasted file paths will have backward slashes and would need to be changed accordingly.

Value

A data.frame with columns; Descriptor and Value.

Author(s)

Anthony Hammond

Examples

```
#Import catchment descriptors from a NRFA peakflows xml file and display in console
## Not run: CDs.4003 <- CDsXML("C:/Data/NRFAPeakFlow_v11/Suitable for QMED/4003.xml")
## Not run: CDs.4003
#Import catchment descriptors from a FEH webserver xml file and display xml in the console
## Not run: CDs.MySite <- CDsXML("C:/Data/FEH_Catchment_384200_458200.xml")
```

DDF*DDF results from a DDFImport object*

Description

Extracts results from a data frame imported using the DDFImport function

Usage

```
DDF(x, duration, RP = 100)
```

Arguments

x	A data frame of DDF13 or DDF22 results imported using the DDFImport function
duration	the duration (hrs) for which a rainfall depth estimate is required
RP	the return period (years) for which a rainfall depth estimate is required

Details

The .xml files only provide a set number of durations and return periods for DDF13 and DDF22. This function optimises the GEV distribution on the results in order to interpolate across return periods. A linear interpolation is used between durations. The interpolation method may provide results that differ from the FEH webserver in the region of 0.1mm. The result is then rounded to an integer.

Value

A DDF13 or DDF22 estimate of rainfall depth (mm)

Author(s)

Anthony Hammond

Examples

```
#Get DDF13 results from a the DDF
## Not run: DDF13.4003 <- DDFImport("C:/Data/NRFAPeakFlow_v9/Suitable for QMED/04003.xml")
#Estimate the 20-year, 5 hour depth
## Not run: DDF(DDF13.4003, duration = 5, RP = 20)
```

DDF99

*FEH99 depth duration frequency precipitation model***Description**

Estimation of design rainfall depths, and the rarity of observed rainfall

Usage

```
DDF99(Duration, RP, pars, Depth = NULL, disc = NULL)
```

Arguments

Duration	numeric. The duration of interest (in hours)
RP	return period
pars	a numeric vector of length six. The six catchment parameters for the DDF model in the order of: c, d1, d2, d3, e, f
Depth	a user supplied rainfall depth for the duration under question
disc	converts from the sliding duration to fixed duration estimate. Choices are "hourly" or "daily"

Details

The depth duration frequency rainfall model is detailed in the Flood Estimation Handbook (1999), volume 2. A note about the discretisation: The user can choose between "daily" or "hourly" for the sliding duration to fixed duration conversion. If the 'Depth' argument is used, it overrides the return period (RP) argument and provides RP as a function of depth. However, if both the 'Depth' and the 'disc' arguments are used, the sliding duration depth is provided as a function of the user input depth. This resulting depth can then be used without the 'disc' argument to determine the sliding duration RP.

Value

the rainfall depth or rainfall return period

Author(s)

Anthony Hammond

Examples

```
#Examples from FEH volume 2
#The parameters for these examples are from FEH v2
#What is the 2-day rainfall with return period 100-years for Norwich.
DDF99(Duration = 48, RP = 100, pars = c(-0.023, 0.273, 0.351, 0.236, 0.309, 2.488))
#What is the 4-hour rainfall with return period 20 years for a typical point in the Lyne catchment
DDF99(Duration = 4, RP = 20, pars = c(-0.025, 0.344, 0.485, 0.402, 0.287, 2.374))
```

```
#How rare was the rainfall of 6th August 1978 at Broughshane, County Antrim?  
DDF99(Duration = 5, Depth = 47.7, pars = c(-0.022, 0.412, 0.551, 0.276, 0.261, 2.252))
```

DDF99Pars

DDF99 parameters from .xml files

Description

Imports the FEH 1999 depth duration frequency parameters from xml files either from an FEH webservice download or from the Peakflows dataset downloaded from the national river flow archive (NRFA) website

Usage

```
DDF99Pars(x)
```

Arguments

x the xml file path

Details

This function is coded to import DDF99 parameters from xml files from the NRFA or the FEH webserver. File paths for importing data require forward slashes. On some operating systems, such as windows, the copy and pasted file paths will have backward slashes and would need to be changed accordingly.

Value

A list with two elements, each a data frame with columns; parameters and associated Values The first data frame is for the catchment average parameters (these still require an ARF adjustment where appropriate) and the second for the 1km2 grid point parameters.

Author(s)

Anthony Hammond

Examples

```
#Import DDF99 parameters from a NRFA peakflows xml file and display in console  
## Not run: DDF99.4003 <- DDF99Pars("C:/Data/NRFAPeakFlow_v11/Suitable for QMED/04003.xml")  
## Not run: DDF99.4003  
#Import DDF99 parameters from a FEH webserver xml file and display in the console  
## Not run: DDF99.MySite <- DDF99Pars("C:/Data/FEH_Catchment_384200_458200.xml")
```

DDFImport

DDF13 or DDF22 results from .xml files

Description

Imports the depth duration frequency 2013 or 2022 results from xml files either from an FEH webservice download or from the Peakflows dataset downloaded from the national river flow archive (NRFA) website

Usage

```
DDFImport(x, ARF = FALSE, Plot = TRUE, DDFVersion = 22)
```

Arguments

x	the xml file path
ARF	logical argument with a default of FALSE. If TRUE, the areal reduction factor is applied to the results. If FALSE, no area reduction factor is applied
Plot	logical argument with a default of TRUE. If TRUE the DDF curve is plotted for a few return periods
DDFVersion	Version of the DDF model (numeric). either 22 or 13. The default is 22.

Details

This function returns a data-frame of results. For further durations and return periods the separate DDF function can be applied with the data-frame as the argument/input. File paths for importing data require forward slashes. On some operating systems, such as windows, the copy and pasted file paths will have backward slashes and would need to be changed accordingly.

Value

A data frame of DDF results (mm) with columns for duration and rows for return period. If Plot equals TRUE a DDF plot is also returned.

Author(s)

Anthony Hammond

Examples

```
#Import DDF22 results from a NRFA peakflows xml file and display in console
## Not run: DDF22.4003 <- DDFImport("C:/Data/NRFAPeakFlow_v11/Suitable for QMED/04003.xml")
## Not run: DDF22.4003
#Import DDF22 results from a FEH webserver xml file and display in the console
## Not run: DDF22.MySite <- DDFImport("C:/Data/FEH_Catchment_384200_458200.xml")
```


DesHydro

*Design hydrograph extraction***Description**

Extracts a mean hydrograph from a flow series

Usage

```
DesHydro(
  x,
  qu = 0.8,
  n = 10,
  thr = 0.975,
  xst = NULL,
  xend = NULL,
  RetAll = FALSE,
  Smooth = 1
)
```

Arguments

x	a numeric vector. The flow series of interest
qu	the quantile of flow which separates peaks and truncates either side of the peak to form the event hydrograph. The default is 0.8
n	number of event hydrographs from which to derive the mean hydrograph. Default is 10. Depending on the length of x, there may be less than 10
thr	threshold above which event peaks are selected. The default is 0.975
xst	an integer to truncate the x axis of the plot and resulting design hydrograph. The first point of the design hydrograph
xend	an integer to truncate the x axis of the plot and resulting design hydrograph. The last point of the design hydrograph
RetAll	logical argument with a default of false. If TRUE, all the hydrographs from which the mean is derived are returned in a data.frame. If FALSE, the mean hydrograph is returned
Smooth	an integer (from 0 to 5). To smooth the design hydrograph. The default is 1 which provides the minimum level of smoothing. 0 is no smoothing and 5 is the highest

Details

All the peaks over a user defined threshold are identified and separated by a user defined value 'qu', which is a quantile of flow. The top n peaks are selected and the hydrographs extracted. Each hydrograph is centred on the peak and truncated either side, where the flow falls below the 'qu' quantile flow. All events are scaled to have a peak flow of one, and the mean of these is taken as

the scaled design hydrograph. After an initial view of the hydrograph, it can be truncated using the 'xst' and 'xend' arguments. The default is to select 10 hydrographs for averaging, however, there may well be fewer if the sample is short.

Value

a numeric vector which is the mean of the top n peak events in the flow series. Also a plot of the n hydrographs and the design hydrograph. If the RetAll argument equals TRUE, a data.frame of the n hydrographs is returned instead.

Note

The smoothing is done by rolling average, where the the mean is of points from n to the left up to n to the right. The n is chosen by the Smooth argument.

Author(s)

Anthony Hammond

Examples

```
#Extract a design hydrograph from the Thames daily mean flow. Then print the resulting hydrograph
ThamesDesHydro <- DesHydro(ThamesPQ$Q)
ThamesDesHydro
#Do the same but truncate the design hydrograph and the plot from the first point to the 30th
DesHydro(ThamesPQ$Q, xst = 1, xend = 30)
#adjust the qu value to see the impact
ThamesDesHydro <- DesHydro(ThamesPQ$Q, qu = 0.7)
#Return all the hydrographs
ThamesHydros <- DesHydro(ThamesPQ$Q, xst = 1, xend = 30, RetAll = TRUE)
#view the first six rows of the hydrographs
head(ThamesHydros)
```

DeTrend

Linearly detrend a sample

Description

Applies a linear detrend to a sample

Usage

```
DeTrend(x)
```

Arguments

x a numeric vector

Details

Adjusts all the values in the sample, of size n , by the difference between the linearly modelled i th data point and the linearly modelled n th data point.

Value

A numeric vector which is a linearly detrended version of x .

Author(s)

Anthony Hammond

Examples

```
# Get an annual maximum (AM) sample that looks to have a significant trend
AM.21025 <- GetAM(21025)
# plot the resulting AM as a bar plot. Then detrend and compare with another plot
plot(AM.21025$Flow, type = "h", ylab = "Discharge (m3/s)")
AM.Detrend <- DeTrend(AM.21025$Flow)
plot(AM.Detrend, type = "h", ylab = "Discharge (m3/s)")
```

DiagPlots

Diagnostic plots for pooling groups

Description

Provides 10 plots to compare the sites in the pooling group

Usage

```
DiagPlots(x, gauged = FALSE)
```

Arguments

<code>x</code>	pooling group derived from the <code>Pool()</code> function
<code>gauged</code>	logical argument with a default of <code>FALSE</code> . <code>TRUE</code> adds the top site in the pooling group to the plots in a different colour

Value

ten diagnostic plots for pooling groups

Author(s)

Anthony Hammond

Examples

```
#Form a gauged pooling group and plot the diagnostics with gauged = TRUE
Pool.28015 <- Pool(GetCDs(28015))
DiagPlots(Pool.28015, gauged = TRUE)
#Form an ungauged pooling group and plot the diagnostics
Pool.28015 <- Pool(GetCDs(28015), exclude = 28015)
DiagPlots(Pool.28015)
```

DonAdj

Donor adjustment candidates & results

Description

Provides donor adjustment candidates, descriptors, and results in order of the proximity to the centroid of the subject catchment.

Usage

```
DonAdj(CDs = NULL, x, y, QMEDscd = NULL, alpha = TRUE, rows = 10, d2 = NULL)
```

Arguments

CDs	catchment descriptors derived from either GetCDs or CDsXML
x	catchment centroid easting (for when CDs isn't used)
y	catchment centroid northing (for when CDs isn't used)
QMEDscd	QMED estimate for the catchment of interest (for when CDs isn't used)
alpha	logical argument with a default of TRUE. If FALSE the exponent of the donor adjustment equation is set to one
rows	number of sites provided; default is 10
d2	a numeric vector of length two; the two site references for the donor catchments chosen for the two donor case

Details

When d2 is FALSE the results for single donor adjustment are in the final column headed 'QMED.adj' for each site. If alpha is set to FALSE, the results in this column are from the same donor equation but with an exponent of 1. The donor adjustment method is as outlined in Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation. The method for two donors is outlined in 'Kjeldsen, T. (2019). Adjustment of QMED in ungauged catchments using two donor sites. *Circulation - The Newsletter of the British Hydrological Society*, 4'. When two donors are used, only the result is returned, rather than donor candidates. The QMEDfse column provides the gauged factorial standard error for the median of the annual maximum sample. It is worth considering this when choosing a donor site (a high value indicates a poor donor). When choosing between two donors, the site with a lower QMEDfse would be an appropriate choice (all else being equal). The QMEDfse is calculated with the QMEDfseSS() function.

Value

A data.frame with rownames of site references and columns of catchment descriptors, distance from subject site, and associated results. When two donors are used, only the resulting adjusted QMED is returned

Author(s)

Anthony Hammond

Examples

```
#Get some CDs and output candidate donor sites
CDs.54022 <- GetCDs(54022)
DonAdj(CDs.54022)
#Get results with inputs of x,y, and QMEDscd
DonAdj(x = 283261, y = 288067, QMEDscd = 17.931)
#Get a result with two donors
DonAdj(CDs.54022, d2 = c(54092, 54091))
```

EncProb

Encounter probabilities

Description

Calculates the probability of experiencing at least n events with a given return period (RP), over a given number of years

Usage

```
EncProb(n, yrs, RP, dist = "Poisson")
```

Arguments

n	number of events
yrs	number of years
RP	return period of the events
dist	choice of probability distribution. Either "Poisson" or "Binomial"

Details

The choice of binomial or Poisson distributions for calculating encounter probabilities is akin to annual maximum (AM) versus peaks over threshold (POT) approaches to extreme value analysis. AM and binomial assume only one "event" can occur in the blocked time period. Whereas Poisson and POT don't make this assumption. In the case of most catchments in the UK, it is rare to have less than two independent "events" per year; in which case the Poisson and POT choices are more suitable. In large catchments, with seasonally distinctive baseflow, there may only be one independent peak in the year. However, the results from both methods converge with increasing magnitude, yielding insignificant difference beyond a 20-year return period.

Value

A probability

Author(s)

Anthony Hammond

Examples

```
#Calculate the probability of exceeding at least one 50-yr RP event
#over a 10 year period, using the Poisson distribution.
EncProb(n = 1, yrs = 10, RP = 50)
#Calculate the probability of exceeding at least two 100-yr RP events
#over a 100 year period, using the binomial distribution.
EncProb(n = 2, yrs = 100, RP = 100, dist = "Binomial")
```

ERPlot

Extreme rank plot

Description

A plot to inspect the distribution of ordered data

Usage

```
ERPlot(x, dist = "GenLog", main = NULL, Pars = NULL, GF = NULL)
```

Arguments

x	numeric vector. A sample for inspection
dist	a choice of distribution. The choices are "GenLog" (the default), "GEV", "Kappa3", "Gumbel", and "GenPareto"
main	a character string to change the default title, which is the distribution choice.
Pars	a vector of parameters for the distribution. In the order of location, scale, & shape (ignoring the latter if Gumbel). If left null the parameters are estimated from x.
GF	a vector of length growth curve parameters, in the order of; Lcv, LSkew and Median (ignoring the LSkew if Gumbel).

Details

This plot compares the simulated flows for each rank of the sample with the observed flows of the same rank. 500 simulated flows for each rank are plotted and the mean of these is highlighted in red. There is a line of perfect fit so you can see how much this "cloud" of simulation differs from the observed. By default the parameters of the distribution for comparison with the sample are estimated from the sample. However, the pars argument can be used to compare the distribution with

parameters estimated separately. Similarly the growth factor (GF) parameters, linear coefficient of variation (Lcv) & linear skewness (LSkew) with the median can be entered. In this way the pooling estimated distribution can be compared to the sample. This ERplot is an updated version of that described in Hammond, A. (2019). Proposal of the 'extreme rank plot' for extreme value analysis: with an emphasis on flood frequency studies. *Hydrology Research*, 50 (6), 1495–1507.

Value

The extreme rank plot as described in the details

Author(s)

Anthony Hammond

Examples

```
#Get an AMAX sample and plot
AM.27083 <- GetAM(27083)
ERPlot(AM.27083$Flow)
#Get a pooled estimate of Lcv & LSkew to use with the GF argument
QuickResults(GetCDs(27083), gauged = TRUE)
#Use the resulting Lcv, Lskew and RP2 for the GF argument and change the title
ERPlot(AM.27083$Flow, main = "Site 27083 pooled comparison", GF = c(0.23, 0.17, 12))
```

EVPlot

Extreme value plot (frequency and growth curves)

Description

Plots the extreme value frequency curve or growth curve with observed sample points.

Usage

```
EVPlot(  
  x,  
  dist = "GenLog",  
  scaled = TRUE,  
  Title = "Extreme value plot",  
  ylabel = NULL,  
  LineName = NULL,  
  Unc = TRUE  
)
```

Arguments

x	a numeric vector. The sample of interest
dist	a choice of distribution. "GEV", "GenLog", "Kappa3", "Gumbel" or "GenPareto". The default is "GenLog"
scaled	logical argument with a default of TRUE. If TRUE the plot is a growth curve (scaled by the QMED). If FALSE, the plot is a frequency curve
Title	a character string. The user chosen plot title. The default is "Extreme value plot"
ylabel	a character string. The user chosen label for the y axis. The default is "Q/QMED" if scaled = TRUE and "Discharge (m3/s)" if scaled = FALSE
LineName	a character string. User chosen label for the plotted curve
Unc	logical argument with a default of TRUE. If TRUE, 95 percent uncertainty intervals are plotted.

Details

The plotting has the option of generalised extreme value (GEV), generalised Pareto (GenPareto), Gumbel, or generalised logistic (GenLog) distributions. The uncertainty is quantified by bootstrapping.

Value

An extreme value plot (frequency or growth curve) with intervals to quantify uncertainty

Author(s)

Anthony Hammond

Examples

```
#Get an AMAX sample and plot the growth curve with the GEV distribution
AM.203018 <- GetAM(203018)
EVPlot(AM.203018$Flow, dist = "GEV")
```

EVPlotAdd

Add lines and/or points to an extreme value plot

Description

Functionality to add extra lines or points to an extreme value plot (derived from the EVPlot function).

Usage

```
EVPlotAdd(
  Pars,
  dist = "GenLog",
  Name = "Adjusted",
  MED = NULL,
  xyleg = NULL,
  col = "red",
  lty = 1,
  pts = NULL,
  ptSym = NULL
)
```

Arguments

Pars	a numeric vector of length two. The first is the Lcv (linear coefficient of variation) and the second is the Lskew (linear skewness).
dist	distribution name with a choice of "GenLog", "GEV", "GenPareto", "Kappa3", and "Gumbel"
Name	character string. User chosen name for points or line added (for the legend)
MED	The two year return level. Necessary In the case where the EV plot is not scaled
xyleg	a numeric vector of length two. They are the x and y position of the symbol and text to be added to the legend.
col	The colour of the points of line that have been added
lty	An integer. The type of line added
pts	A numeric vector. An annual maximum sample, for example. This is for points to be added
ptSym	An integer. The symbol of the points to be added

Details

A line can be added using the Lcv and Lskew based on one of four distributions (Generalised extreme value, Generalised logistic, Gumbel, Generalised Pareto). Points can be added as a numeric vector. If a single point is required, the base points() function can be used and the x axis will need to be $\log(RP-1)$.

Value

Additional, user specified line or points to an extreme value plot derived from the EVPlot function.

Author(s)

Anthony Hammond

Examples

```
#Get an AMAX sample and plot the growth curve with the GEV distribution
AM.203018 <- GetAM(203018)
EVPlot(AM.203018$Flow, dist = "GEV")
#Now add a line (dotted & red) for the generalised logistic distribution
#first get the Lcv and Lskew using the Lmoms function
pars <- as.numeric(Lmoms(AM.203018[,2])[c(5,6)])
EVPlotAdd(Pars = pars, dist = "GenLog", Name = "GenLog", xyleg = c(-5.2,2.65), lty = 3)
#Now add a line for the gumbel distribution which is darkgreen and dashed.
EVPlotAdd(Pars = pars[1], dist = "Gumbel", Name = "Gumbel",
xyleg = c(-5.19,2.5), lty = 3, col = "darkgreen")
#now plot afresh and get another AMAX and add the points
EVPlot(AM.203018$Flow, dist = "GEV")
AM.27090 <- GetAM(27090)
EVPlotAdd(xyleg = c(-4.9,2.65), pts = AM.27090[,2], Name = "27090")
```

EVPool

Extreme value plot for pooling groups

Description

Plots the extreme value frequency curve or growth curve for gauged or ungauged pooled groups

Usage

```
EVPool(
  x,
  AMAX = NULL,
  gauged = FALSE,
  dist = "GenLog",
  QMED = NULL,
  Title = "Pooled growth curve",
  UrbAdj = FALSE,
  CDs
)
```

Arguments

x	pooling group derived from the Pool() function
AMAX	the AMAX sample to be plotted in the case of gauged. If NULL, & gauged equals TRUE, the AMAX from the first site in the pooling group is used
gauged	logical argument with a default of FALSE. If FALSE, the plot is the ungauged pooled curve accompanied by the single site curves of the group members. If TRUE, the plot is the gauged curve and single site curve with the observed points added
dist	a choice of distribution. Choices are "GEV", "GenLog", "Kappa3", or "Gumbel". The default is "GenLog"

QMED	a chosen QMED to convert the curve from a growth curve to the frequency curve
Title	a character string. The user chosen plot title. The default is "Pooled growth curve"
UrbAdj	a logical argument with a default of FALSE. If TRUE and urban adjustment is applied to the pooled growth curve
CDs	catchment descriptors derived from either GetCDs or CDsXML. Only necessary if UrbAdj is TRUE

Value

An extreme value plot for gauged or ungauged pooling groups

Author(s)

Anthony Hammond

Examples

```
#Get some CDs, form an ungauged pooling group and apply EVPlot.
CDs.28015 <- GetCDs(28015)
Pool.28015 <- Pool(CDs.28015, exclude = 28015)
EVPool(Pool.28015)
#Do the same for the gauged case, change the title, and convert with a QMED of 105.5.
PoolG.28015 <- Pool(CDs.28015)
EVPool(PoolG.28015, gauged = TRUE, Title = "Gauged frequency curve - Site 28015", QMED = 9.8)
#Pretend we have an extra AMAX for the gauge. Amend the pooling group Lcv and LSkew
#for the site accordingly then apply EVPool with the updated AMAX.
#Firstly, get the AMAX sample
AM.28015 <- GetAM(28015)
#Add an extra AMAX flow of 15m3/s
Append28015 <- append(AM.28015$Flow, 15)
#Amend the Lcv and Lskew in the pooling group
PoolG.28015[1, c(16, 17)] <- c(Lcv(Append28015), LSkew(Append28015))
#Now plot gauged with the updated AMAX
EVPool(PoolG.28015, AMAX = Append28015, gauged = TRUE)
```

GenLogAM

Generalised logistic distribution - estimates directly from sample

Description

Estimated quantiles as a function of return period (RP) and vice versa, directly from the data

Usage

```
GenLogAM(x, RP = 100, q = NULL)
```

Arguments

x	numeric vector (block maxima sample)
RP	return period (default = 100)
q	quantile (magnitude of variable)

Details

If the argument q is used, it overrides RP and provides RP as a function of q (magnitude of variable) as opposed to q as a function of RP. The parameters are estimated by the method of L-moments, as detailed in 'Hosking J. Wallis J. 1997 Regional Frequency Analysis: An Approach Based on L-moments. Cambridge University Press, New York'.

Value

quantile as a function of RP or vice versa.

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample and estimate the 50-year RP
AM.27090 <- GetAM(27090)
GenLogAM(AM.27090$Flow, RP = 50)
#Estimate the RP for a 600m3/s discharge
GenLogAM(AM.27090$Flow, q = 600)
```

GenLogEst

Generalised logistic distribution estimates from parameters

Description

Estimated quantiles as function of return period (RP) and vice versa, from user input parameters

Usage

```
GenLogEst(loc, scale, shape, q = NULL, RP = 100)
```

Arguments

loc	location parameter
scale	scale parameter
shape	shape parameter
q	quantile. magnitude of the variable under consideration
RP	return period

Details

If the argument `q` is used, it overrides `RP` and provides `RP` as a function of `q` (magnitude of variable) as opposed to `q` as a function of `RP`.

Value

quantile as a function of `RP` or vice versa

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample, estimate the parameters and estimate 50-year RP
AM.27090 <- GetAM(27090)
GenLogPars(AM.27090$Flow)
#Store parameters in an object
Pars <- as.numeric(GenLogPars(AM.27090$Flow))
#get estimate of 50-yr flow
GenLogEst(Pars[1], Pars[2], Pars[3], RP = 50)
#Estimate the RP for a 600m3/s discharge
GenLogEst(Pars[1], Pars[2], Pars[3], q = 600)
```

GenLogGF

Generalised logistic distribution growth factors

Description

Estimated growth factors as a function of return period, with inputs of `Lcv` & `LSkew` (linear coefficient of variation & linear skewness)

Usage

```
GenLogGF(lcv, lskew, RP)
```

Arguments

<code>lcv</code>	linear coefficient of variation
<code>lskew</code>	linear skewness
<code>RP</code>	return period

Details

Growth factors are calculated by the method outlined in the Flood Estimation Handbook, volume 3, 1999.

Value

Generalised logistic estimated growth factor

Author(s)

Anthony Hammond

Examples

```
#Estimate the 50-year growth factors from an Lcv and Lskew of 0.17 and 0.04, respectively.
GenLogGF(0.17, 0.04, RP = 50)
```

GenLogPars

Generalised logistic distribution parameter estimates

Description

Estimated parameters from a sample (with Lmoments or maximum likelihood estimation) or from L1 (first L-moment), Lcv (linear coefficient of variation), and LSkew (linear skewness)

Usage

```
GenLogPars(x = NULL, mle = FALSE, L1, LCV, LSKEW)
```

Arguments

x	numeric vector. The sample
mle	logical argument with a default of FALSE. If FALSE the parameters are estimated with Lmoments, if TRUE the parameters are estimated by maximum likelihood estimation.
L1	first Lmoment
LCV	linear coefficient of variation
LSKEW	linear skewness

Details

The L-moment estimated parameters are by the method detailed in 'Hosking J. Wallis J. 1997 Regional Frequency Analysis: An Approach Based on L-moments. Cambridge University Press, New York'

Value

Parameter estimates (location, scale, shape)

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample and estimate the parameters using Lmoments
AM.27090 <- GetAM(27090)
GenLogPars(AM.27090$Flow)
#Estimate parameters using MLE
GenLogPars(AM.27090$Flow, mle = TRUE)
#calculate Lmoments and estimate the parameters with L1, Lcv and Lskew
Lmoms(AM.27090$Flow)
#store linear moments in an object
LPars <- as.numeric(Lmoms(AM.27090$Flow))[c(1,5,6)]
GenLogPars(L1 = LPars[1], LCV = LPars[2], LSKEW = LPars[3])
```

GenParetoEst

*Generalised Pareto distribution estimates from parameters***Description**

Estimated quantiles as function of return period (RP) and vice versa, from user input parameters

Usage

```
GenParetoEst(loc, scale, shape, q = NULL, RP = 100, ppy = 1)
```

Arguments

loc	location parameter
scale	scale parameter
shape	shape parameter
q	quantile. magnitude of the variable under consideration
RP	return period
ppy	peaks per year. Default is one

Details

If the argument q is used, it overrides RP and provides RP as a function of q (magnitude of variable) as opposed to q as a function of RP. The average number of peaks per year argument (ppy) is for the function to convert from the peaks over threshold (POT) scale to the annual scale. For example, if there are 3 peaks per year, the probability associated with the 100-yr return period estimate would be $0.01/3$ (i.e. an RP of 300 on the POT scale) rather than 0.01.

Value

quantile as a function of RP or vice versa

Author(s)

Anthony Hammond

Examples

```
#Get a POT sample, estimate the parameters, and estimate 50-year RP
ThamesPOT <- POTextract(ThamesPQ[,c(1,3)], thresh = 0.90)
GenParetoPars(ThamesPOT$peak)
#Store parameters in an object
Pars <- as.numeric(GenParetoPars(ThamesPOT$peak))
#get estimate of 50-yr flow
GenParetoEst(Pars[1], Pars[2], Pars[3], ppy = 1.867, RP = 50)
#Estimate the RP for a 600m3/s discharge
GenParetoEst(Pars[1], Pars[2], Pars[3], ppy = 1.867, q = 600)
```

 GenParetoGF

Generalised Pareto distribution growth factors

Description

Estimated growth factors as a function of return period, with inputs of Lcv & LSkew (linear coefficient of variation & linear skewness)

Usage

```
GenParetoGF(lcv, lskew, RP, ppy = 1)
```

Arguments

lcv	linear coefficient of variation
lskew	linear skewness
RP	return period
ppy	peaks per year

Details

Growth factors (GF) are calculated by the method outlined in the Flood Estimation Handbook, volume 3, 1999. The average number of peaks per year argument (ppy) is for the function to convert from the peaks over threshold (POT) scale to the annual scale. For example, if there are 3 peaks per year, the probability associated with the 100-yr return period estimate would be 0.01/3 (i.e. an RP of 300 on the POT scale) rather than 0.01.

Value

Generalised Pareto estimated growth factor

Author(s)

Anthony Hammond

Examples

```
#Get POT flow data from the Thames at Kingston (noting the no. peaks per year).
#Then estimate the 100-year growth factor with lcv and lskew estimates
TPOT <- POTextract(ThamesPQ[,c(1,3)], thresh = 0.90)
GenParetoGF(Lcv(TPOT$peak), LSkew(TPOT$peak), RP = 100, ppy = 1.867)
#multiply by the median of the POT data for an estimate of the 100-yr flood
GenParetoGF(Lcv(TPOT$peak), LSkew(TPOT$peak), RP = 100, ppy = 1.867)*median(TPOT$peak)
```

GenParetoPars

*Generalised Pareto distribution parameter estimates***Description**

Estimated parameters from a sample (with Lmoments or maximum likelihood estimation) or from L1 (first L-moment), Lcv (linear coefficient of variation), and LSkew (linear skewness)

Usage

```
GenParetoPars(x = NULL, mle = FALSE, L1, LCV, LSKEW)
```

Arguments

x	numeric vector. The sample
mle	logical argument with a default of FALSE. If FALSE the parameters are estimated with Lmoments, if TRUE the parameters are estimated by maximum likelihood estimation
L1	first Lmoment
LCV	linear coefficient of variation
LSKEW	linear skewness

Details

The L-moment estimated parameters are by the method detailed in 'Hosking J. Wallis J. 1997 Regional Frequency Analysis: An Approach Based on L-moments. Cambridge University Press, New York'

Value

Parameter estimates (location, scale, shape)

Author(s)

Anthony Hammond

Examples

```
#Get a peaks over threshold sample and estimate the parameters using Lmoments
ThamesPOT <- ThamesPOT <- POTextract(ThamesPQ[,c(1,3)], thresh = 0.90)
GenParetoPars(ThamesPOT$peak)
#Estimate parameters using MLE
GenParetoPars(ThamesPOT$peak, mle = TRUE)
#calculate Lmoments and estimate the parameters with L1, Lcv and Lskew
Lmoms(ThamesPOT$peak)
#store linear moments in an object
LPars <- as.numeric(Lmoms(ThamesPOT$peak))[c(1,5,6)]
GenParetoPars(L1 = LPars[1], LCV = LPars[2], LSKEW = LPars[3])
```

 GenParetoPOT

Generalised Pareto distribution - estimates directly from sample

Description

Estimated quantiles as function of return period (RP) and vice versa, directly from the data

Usage

```
GenParetoPOT(x, ppy = 1, RP = 100, q = NULL)
```

Arguments

x	numeric vector (block maxima sample)
ppy	peaks per year
RP	return period (default = 100)
q	quantile (magnitude of variable)

Details

If the argument q is used, it overrides RP and provides RP as a function of q (magnitude of variable) as opposed to q as a function of RP. The average number of peaks per year argument (ppy) is for the function to convert from the peaks over threshold (POT) scale to the annual scale. For example, if there are 3 peaks per year, the probability associated with the 100-yr return period estimate would be 0.01/3 (i.e. an RP of 300 on the POT scale) rather than 0.01. The parameters are estimated by the method of L-moments, as detailed in 'Hosking J. Wallis J. 1997 Regional Frequency Analysis: An Approach Based on L-moments. Cambridge University Press, New York'.

Value

quantile as a function of RP or vice versa

Author(s)

Anthony Hammond

Examples

```
#Get a POT series and estimate the 50-year RP
ThamesPOT <- POTextract(ThamesPQ[,c(1,3)], thresh = 0.90)
GenParetoPOT(ThamesPOT$peak, ppy = 1.867, RP = 50)
#Estimate the RP for a 600m3/s discharge
GenParetoPOT(ThamesPOT$peak, ppy = 1.867, q = 600)
```

GetAM	<i>Get an annual maximum sample from the National River Flow Archive sites suitable for pooling</i>
-------	---

Description

Extracts the annual maximum peak flow sample and associated dates for the site of interest.

Usage

```
GetAM(ref)
```

Arguments

ref the site reference of interest (numeric)

Value

A data.frame with columns; Date, Flow, and id

Author(s)

Anthony Hammond

Examples

```
#Get an AMAX sample and display it in the console
GetAM(203018)
#Save an AMAX sample as an object
AM.203018 <- GetAM(203018)
```

GetCDs	<i>Get catchment descriptors from the National River Flow Archive sites considered suitable for median annual maximum flow estimation (QMED) and pooling.</i>
--------	---

Description

Extracts the catchment descriptors for a site of interest from those suitable for QMED and pooling.

Usage

```
GetCDs(x)
```

Arguments

x the site reference of interest (numeric)

Value

A data.frame with columns; Descriptor and Value.

Author(s)

Anthony Hammond

Examples

```
#Get CDs and display in the console
CDs.203018 <- GetCDs(203018)
CDs.203018
```

GetMetOffice	<i>Get regional Met Office average temperature or rainfall series (monthly, seasonal, and annual).</i>
--------------	--

Description

Extracts regional mean temperature or rainfall from the met office UK & regional series. The total duration of bright sunshine is also available.

Usage

```
GetMetOffice(Variable, Region)
```

Arguments

Variable	Either Tmean, Rainfall, or Sunshine
Region	One of "UK", "England", "Wales", "Scotland", "Northern_Ireland", "England_and_Wales", "England_N", "England_S", "Scotland_N", "Scotland_E", "Scotland_W", "England_E_and_NE", "England_NW_and_N_Wales", "Midlands", "East_Anglia", "England_SW_and_S_Wales", "England_SE_and_Central_S".

Details

The function returns time series data from the 19th century through to the present month.

Value

A data.frame with 18 columns; year, months, seasons, and annual. Rows then represent each year of the timeseries.

Author(s)

Anthony Hammond

Examples

```
#Get the Rainfall series for the UK
## Not run: UKRain <- GetMetOffice(Variable = "Rainfall", Region = "UK")
#Now we'll get mean temperature data for East Anglia
## Not run: TempEastAnglia <- GetMetOffice(Variable = "Tmean", Region = "East_Anglia")
```

GetNRFA

Get National River Flow Archive data using gauge ID.

Description

Extracts NRFA data using the API.

Usage

```
GetNRFA(ID, Type = "Q")
```

Arguments

ID	ID number of the gauge of interest.
Type	Type of data required. One of "Q", "P", "PQ", "Gaugings", or "AMAX".

Details

The function can be used to get daily catchment rainfall or mean flow, or both together (concurrent). It can also be used to get gaugings and amax data. Note that the latter has rejected years included (check the gauge on the associated NRFA web page for details).

Value

A data.frame with date in the first columns and variable/s of interest in the remaining column/s.

Author(s)

Anthony Hammond

Examples

```
#Get the concurrent rainfall and mean flow series for the Tay at Ballathie (site 15006).  
## Not run: BallathiePQ <- GetNRFA(15006, "PQ")  
#Now we'll get the gaugings  
## Not run: BallathieGaugings <- GetNRFA(15006, "Gaugings")
```

GetQMED

QMED from a gauged site suitable for QMED

Description

Provides QMED (median annual maximum flow) from a site suitable for QMED, using the site reference.

Usage

```
GetQMED(x)
```

Arguments

x the gauged reference

Value

the median annual maximum

Author(s)

Anthony Hammond

Examples

```
#Get the observed QMED from sites 55002  
GetQMED(55002)
```

 GetRainEA

Get Environment Agency rainfall data (England).

Description

Extract rainfall data from the Environment Agency's API.

Usage

```
GetRainEA(
  Lat = 54,
  Lon = -2,
  Range = 10,
  WISKI_ID = NULL,
  Period = 0.25,
  DateSt = "2015-12-01",
  DateEnd = "2015-12-31"
)
```

Arguments

Lat	Latitude of the point of interest. Provided when the user wants information about available local rain gauges
Lon	Longitude of the point of interest. Provided when the user wants information about available local rain gauges
Range	The radius (km) from the point of interest (Lat, Lon) for which the user wants rain gauge information.
WISKI_ID	The WISKI identification (as "character") for the rain gauge of interest
Period	The sampling rate of the rainfall in hours (generally 0.25 or 24. Default is 0.25 (15 minutes).
DateSt	The start date of the data extraction in the form of "YYYY-MM-DD".
DateEnd	The end date of the data extraction in the form of "YYYY-MM-DD".

Details

The function provides one of two outputs. Either information about available local rain gauges, or the data from a specified gauge (specified by WISKI ID). The process is to find the local information (including WISKI ID) by using the latitude and longitude and range. Then use the WISKI ID to get the data. If data requested is not available, for example - outside the date range or not available at the requested sampling rate, an error message is returned stating "no lines available in input". There is currently a 2 million line limit for each use. that is over 5000 years of daily data or 57 years of 15 minute data. However, the 15 minute data can take quite a while and if it takes over 60 seconds a timeout message is returned. hen testing the function I could get 20 years at a time but not 30. Presumably it depends on the connection?

Value

A data.frame with POSIXct (DateTime) in the first column, and rainfall (mm) in the second column. Unless the WISKI_ID is null, then information about rain gauges approximately within a radius (Range) of the Lat and Lon is provided.

Author(s)

Anthony Hammond

Examples

```
#Get information about available rain gauges.
#within a 10km radius of Lat = 54.5, Lon = -3.2
## Not run: RainEA(Lat = 54.5, Lon = -3.2)
#Now we'll use the WISKI reference for the Honister rain gauge
# to get some data for the Dec 2015 (default dates)
## Not run: Honister15 <- RainEA(WISKI_ID = "592463")
#Now we'll have a look at the top of the data and plot it
## Not run: head(Honister15)
## Not run: plot(Honister15, type = "h", ylab = "Rainfall (mm)")
#Now we'll get the daily rain for the same period and plot it
## Not run: Honister24 <- RainEA(WISKI_ID = "592463", Period = 24)
## Not run: plot(Honister24, type = "h", ylab = "Rainfall (mm)")
```

GetRainSEPA

Get Scottish Environment Protection Agency (SEPA) hourly rainfall data.

Description

Extract hourly rainfall data from SEPA's API.

Usage

```
GetRainSEPA(StationName, From = "2022-10-01", To = "ToDate")
```

Arguments

StationName	The name of the station for which you want rainfall. If you type something other than one of the available stations, the list of stations will be returned.
From	A start date for the data in the form of "YYYY-MM-DD".
To	An end date for the data in the form of "YYYY-MM-DD". The default is the most recent date available.

Details

If the "From" date used is significantly before (approx. 30 years) the start of the available data, the function will fail with an error message saying the connection cannot be opened.

Value

A data.frame with POSIXct in the first column, and rainfall in the second column. Unless the StationName provided is not in the available list, then the available list is returned.

Author(s)

Anthony Hammond

Examples

```
#Get the list of available stations
## Not run: RainSEPA("AnythingButAStationName")
#Now we'll get rain from the Bannockburn station
## Not run: Bannockburn <- RainSEPA("Bannockburn", From = "1998-10-01", To = "1998-10-31")
#Now we'll have a look at the top of the data and plot it
## Not run: head(Bannockburn)
## Not run: plot(Bannockburn, type = "h", ylab = "Rainfall (mm)")
```

GEVAM

Generalised extreme value distribution - estimates directly from sample

Description

Estimated quantiles as function of return period (RP) and vice versa, directly from the data

Usage

```
GEVAM(x, RP = 100, q = NULL)
```

Arguments

x	numeric vector (block maxima sample)
RP	return period (default = 100)
q	quantile (magnitude of variable)

Details

If the argument q is used, it overrides RP and provides RP as a function of q (magnitude of variable) as opposed to q as a function of RP. The parameters are estimated by the method of L-moments, as detailed in 'Hosking J. Wallis J. 1997 Regional Frequency Analysis: An Approach Based on L-moments. Cambridge University Press, New York'.

Value

quantile as a function of RP or vice versa.

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample and estimate the 50-year RP
AM.27090 <- GetAM(27090)
GEVAM(AM.27090$Flow, RP = 50)
#Estimate the RP for a 600m3/s discharge
GEVAM(AM.27090$Flow, q = 600)
```

GEVEst

Generalised extreme value distribution estimates from parameters

Description

Estimated quantiles as function of return period (RP) and vice versa, from user input parameters

Usage

```
GEVEst(loc, scale, shape, q = NULL, RP = 100)
```

Arguments

loc	location parameter
scale	scale parameter
shape	shape parameter
q	quantile. magnitude of the variable under consideration
RP	return period

Details

If the argument q is used, it overrides RP and provides RP as a function of q (magnitude of variable) as opposed to q as a function of RP.

Value

quantile as a function of RP or vice versa

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample, estimate the parameters and estimate 50-year RP
AM.27090 <- GetAM(27090)
GEVPars(AM.27090$Flow)
#Store parameters in an object
Pars <- as.numeric(GEVPars(AM.27090$Flow))
#get estimate of 50-yr flow
GEVEst(Pars[1], Pars[2], Pars[3], RP = 50)
#Estimate the RP for a 600m3/s discharge
GEVEst(Pars[1], Pars[2], Pars[3], q = 600)
```

 GEVGF

Generalised extreme value distribution growth factors

Description

Estimated growth factors as a function of return period, with inputs of Lcv & LSkew (linear coefficient of variation & linear skewness)

Usage

```
GEVGF(lcv, lskew, RP)
```

Arguments

lcv	linear coefficient of variation
lskew	linear skewness
RP	return period

Details

Growth factors are calculated by the method outlined in the Flood Estimation Handbook, volume 3, 1999.

Value

Generalised extreme value estimated growth factor

Author(s)

Anthony Hammond

Examples

```
#Estimate the 50-year growth factors from Lcv = 0.17 and Lskew = 0.04
GEVGF(0.17, 0.04, RP = 50)
```

 GEVPars

Generalised extreme value distribution parameter estimates

Description

Estimated parameters from a sample (with Lmoments or maximum likelihood estimation) or from L1 (first L-moment), Lcv (linear coefficient of variation), and LSkew (linear skewness)

Usage

```
GEVPars(x = NULL, mle = FALSE, L1, LCV, LSKEW)
```

Arguments

x	numeric vector. The sample
mle	logical argument with a default of FALSE. If FALSE the parameters are estimated with Lmoments, if TRUE the parameters are estimated by maximum likelihood estimation
L1	first Lmoment
LCV	linear coefficient of variation
LSKEW	linear skewness

Details

The L-moment estimated parameters are by the method detailed in 'Hosking J. Wallis J. 1997 Regional Frequency Analysis: An Approach Based on L-moments. Cambridge University Press, New York'

Value

Parameter estimates (location, scale, shape)

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample and estimate the parameters using Lmoments
AM.27090 <- GetAM(27090)
GEVPars(AM.27090$Flow)
#Estimate parameters using MLE
GEVPars(AM.27090$Flow, mle = TRUE)
#calculate Lmoments and estimate the parameters with L1, Lcv and Lskew
Lmoms(AM.27090$Flow)
#store linear moments in an object
LPars <- as.numeric(Lmoms(AM.27090$Flow))[c(1,5,6)]
GEVPars(L1 = LPars[1], LCV = LPars[2], LSKEW = LPars[3])
```

GoFCompare

Goodness of fit comparison (single sample)

Description

compares the RMSE of four distribution fits for a single AMAX sample.

Usage

```
GoFCompare(x)
```

Arguments

x a numeric vector (your AMAX sample)

Details

This function calculates an RMSE fit score for four distributions (GEV, GenLog, Gumbel, & Kappa3). The lowest RMSE is the best fit. It works as follows. For each distribution: Step1. Simulate 500 samples the same size as x. Step2. Calculate the mean across all 500 samples for each rank to create an ordered central estimate. Step3. Calculate the RMSE between the result of step 2 and the ordered x. Step4. Standardise the RMSE by dividing it by the mean of x and multiply it by 100 (RMSE as a percentage of mean). Note that this is not a hypothesis test. It is only for comparing the fit across the distributions.

Value

A list. The first element is a dataframe with four columns and one row of results. Each column has the standardised RMSE associated with one of the four distributions (GEV, GenLog, Gumbel, Kappa3). The second element is a character string stating the distribution with the best fit.

Author(s)

Anthony Hammond

Examples

```
# Get an AMAX sample then compare the fit..
AM15006 <- GetAM(15006)
GoFCompare(AM15006$Flow)
```

GoFComparePool	<i>Goodness of fit comparison (for a pooling group)</i>
----------------	---

Description

compares the RMSE of four distribution fits for a pooling group.

Usage

```
GoFComparePool(x)
```

Arguments

x a numeric vector (your AMAX sample)

Details

This function calculates an RMSE fit score for four distributions (GEV, GenLog, Gumbel, & Kappa3). The lowest RMSE is the best fit. It works for pooling groups created using the Pool or PoolSmall function. It uses the same method as GoFCompare (see the associated details of that function). It first standardises the pooled AMAX samples (by dividing them by median) and then treats them as a single large sample. Note that this is not a hypothesis test. It is only for comparing the fit across the distributions.

Value

A list. The first element is a dataframe with four columns and one row of results. Each column has the standardised RMSE associated with one of the four distributions (GEV, GenLog, Gumbel, Kappa3). The second element is a character string stating the distribution with the best fit.

Author(s)

Anthony Hammond

Examples

```
# Get a pooling group then compare the fit..
Pool60009 <- Pool(GetCDs(60009))
GoFComparePool(Pool60009)
```

GumbelAM

Gumbel distribution - estimates directly from sample

Description

Estimated quantiles as a function of return period (RP) and vice versa, directly from the data

Usage

```
GumbelAM(x, RP = 100, q = NULL)
```

Arguments

x	numeric vector (block maxima sample)
RP	return period (default = 100)
q	quantile (magnitude of variable)

Details

If the argument q is used, it overrides RP and provides RP as a function of q (magnitude of variable) as opposed to q as a function of RP. The parameters are estimated by the method of L-moments, as detailed in 'Hosking J. Wallis J. 1997 Regional Frequency Analysis: An Approach Based on L-moments. Cambridge University Press, New York'.

Value

quantile as a function of RP or vice versa.

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample and estimate the 50-year RP
AM.27090 <- GetAM(27090)
GumbelAM(AM.27090$Flow, RP = 50)
#Estimate the RP for a 600m3/s discharge
GumbelAM(AM.27090$Flow, q = 600)
```

GumbelEst

Gumbel distribution estimates from parameters

Description

Estimated quantiles as function of return period (RP) and vice versa, from user input parameters

Usage

```
GumbelEst(loc, scale, q = NULL, RP = 100)
```

Arguments

loc	location parameter
scale	scale parameter
q	quantile. magnitude of the variable under consideration
RP	return period

Details

If the argument q is used, it overrides RP and provides RP as a function of q (magnitude of variable) as opposed to q as a function of RP.

Value

quantile as a function of RP or vice versa

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample, estimate the parameters and estimate 50-year RP
AM.27090 <- GetAM(27090)
Pars <- as.numeric(GumbelPars(AM.27090$Flow))
GumbelEst(Pars[1], Pars[2], RP = 50)
#Estimate the RP for a 600m3/s discharge
GumbelEst(Pars[1], Pars[2], q = 600)
```

GumbelGF	<i>Gumbel distribution growth factors</i>
----------	---

Description

Estimated growth factors as a function of return period, with inputs of Lcv & LSkew (linear coefficient of variation & linear skewness)

Usage

```
GumbelGF(lcv, RP)
```

Arguments

lcv	linear coefficient of variation
RP	return period

Details

Growth factors are calculated by the method outlined in the Flood Estimation Handbook, volume 3, 1999.

Value

Gumbel estimated growth factor

Author(s)

Anthony Hammond

Examples

```
#Estimate the 50-year growth factors from an Lcv of 0.17.
GumbelGF(0.17, RP = 50)
```

GumbelPars	<i>Gumbel distribution parameter estimates</i>
------------	--

Description

Estimated parameters from a sample (with Lmoments or maximum likelihood estimation) or from L1 (first L-moment), Lcv (linear coefficient of variation)

Usage

```
GumbelPars(x = NULL, mle = FALSE, L1, LCV)
```

Arguments

x	numeric vector. The sample
mle	logical argument with a default of FALSE. If FALSE the parameters are estimated with Lmoments, if TRUE the parameters are estimated by maximum likelihood estimation
L1	first Lmoment
LCV	linear coefficient of variation

Details

The L-moment estimated parameters are by the method detailed in 'Hosking J. Wallis J. 1997 Regional Frequency Analysis: An Approach Based on L-moments. Cambridge University Press, New York'

Value

Parameter estimates (location, scale)

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample and estimate the parameters using Lmoments
AM.27090 <- GetAM(27090)
GumbelPars(AM.27090$Flow)
#Estimate parameters using MLE
GumbelPars(AM.27090$Flow, mle = TRUE)
#calculate Lmoments and estimate the parameters with L1 and Lcv
Pars <- as.numeric(Lmoms(AM.27090$Flow)[c(1,5)])
GumbelPars(L1 = Pars[1], LCV = Pars[2])
```

H2

Heterogeneity measure (H2) for pooling groups.

Description

Quantifies the heterogeneity of a pooled group

Usage

H2(x, H1 = FALSE)

Arguments

x	pooling group derived from the Pool() function
H1	logical with a default of FALSE. If TRUE, the function applies the 'H1' version of the test (see Hosking & Wallis 1997 reference). If FALSE, the default H2 version is applied.

Details

The H2 measure was developed by Hosking & Wallis and can be found in their book 'Regional Frequency Analysis: an approach based on LMoments (1997). It was also adopted for use by the Flood Estimation Handbook (1999) and is described in volume 3.

Value

A vector of two characters; the first representing the H2 score and the second stating a qualitative measure of heterogeneity.

Author(s)

Anthony Hammond

Examples

```
#Get CDs, form a pooling group and calculate H2
CDs.203018 <- GetCDs(203018)
Pool.203018 <- Pool(CDs.203018)
H2(Pool.203018)
```

HydroPlot

Hydrological plot of concurrent discharge and precipitation

Description

Plots concurrent precipitation and discharge with precipitation along the top and discharge along the bottom

Usage

```
HydroPlot(
  x,
  Title = "Concurrent Rainfall & Discharge",
  from = NULL,
  to = NULL,
  adj.y = 1.5,
  plw = 1,
  qlw = 1.8,
  Return = FALSE
)
```

Arguments

x	a data.frame with three columns in the order of date (or POSIXct), precipitation, and discharge
Title	a character string. The user chosen plot title. The default is "Concurrent Rainfall & Discharge"
from	a starting time for the plot. In the form of a date or POSIXct object. The default is the first row of x
to	an end time for the plot. In the form of a date or POSIXct object. The default is the last row of x
adj.y	a numeric value to adjust the closeness of the precipitation and discharge in the plot. Default is 1.5. A lower value brings them closer and a larger value further apart
plw	a numeric value to adjust the width of the precipitation lines. Default is one. A larger value thickens them and vice versa
qlw	a numeric value to adjust the width of the discharge line. Default is 1.8. A larger value thickens them and vice versa
Return	a logical argument with a default of FALSE. If TRUE the data-frame of time, precipitation, and flow is returned

Details

The input of x is a dataframe with the first column being time. If the data is sub daily this should be class POSIXct with time as well as date.

Value

A plot of concurrent precipitation and discharge. With the former at the top and the latter at the bottom. If the Return argument equals true the associated data-frame is also returned.

Author(s)

Anthony Hammond

Examples

```
#Plot the Thames precipitation and discharge for the 2013 hydrological year,  
#adjusting the y axis to 1.8.  
HydroPlot(ThamesPQ, from = "2013-10-01", to = "2014-09-30", adj.y = 1.8)
```

Kappa3AM

Kappa3 distribution - estimates directly from sample

Description

Estimated quantiles as a function of return period (RP) and vice versa, directly from the data

Usage

```
Kappa3AM(x, RP = 100, q = NULL)
```

Arguments

x	numeric vector (block maxima sample)
RP	return period (default = 100)
q	quantile (magnitude of variable)

Details

If the argument q is used, it overrides RP and provides RP as a function of q (magnitude of variable) as opposed to q as a function of RP. The parameters are estimated by the method of L-moments, as detailed in 'Hosking J. Wallis J. 1997 Regional Frequency Analysis: An Approach Based on L-moments. Cambridge University Press, New York'. The Kappa3 distribution is as defined by This is the Kappa3 distribution as defined in Kjeldsen, T (2019), 'The 3-parameter Kappa distribution as an alternative for use with FEH pooling groups.'Circulation - The Newsletter of the British Hydrological Society, no. 142.

Value

quantile as a function of RP or vice versa.

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample and estimate the 50-year RP
AM.27090 <- GetAM(27090)
Kappa3AM(AM.27090$Flow, RP = 50)
#Estimate the RP for a 600m3/s discharge
Kappa3AM(AM.27090$Flow, q = 600)
```

Kappa3Est

Kappa3 distribution estimates from parameters

Description

Estimated quantiles as function of return period (RP) and vice versa, from user input parameters

Usage

```
Kappa3Est(loc, scale, shape, q = NULL, RP = 100)
```

Arguments

loc	location parameter
scale	scale parameter
shape	shape parameter
q	quantile. magnitude of the variable under consideration
RP	return period

Details

If the argument `q` is used, it overrides `RP` and provides `RP` as a function of `q` (magnitude of variable) as opposed to `q` as a function of `RP`. This is the Kappa3 distribution as defined in Kjeldsen, T (2019), 'The 3-parameter Kappa distribution as an alternative for use with FEH pooling groups.' *Circulation - The Newsletter of the British Hydrological Society*, no. 142.

Value

quantile as a function of RP or vice versa

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample, estimate the parameters and estimate 50-year RP
AM.27090 <- GetAM(27090)
#Get parameters and Store as an object
Pars <- as.numeric(Kappa3Pars(AM.27090$Flow))
#get estimate of 50-yr flow
Kappa3Est(Pars[1], Pars[2], Pars[3], RP = 50)
#Estimate the RP for a 600m3/s discharge
Kappa3Est(Pars[1], Pars[2], Pars[3], q = 600)
```

Kappa3GF

Kappa3 distribution growth factors

Description

Estimated growth factors as a function of return period, with inputs of Lcv & LSkew (linear coefficient of variation & linear skewness)

Usage

```
Kappa3GF(lcv, lskew, RP)
```

Arguments

lcv	linear coefficient of variation
lskew	linear skewness
RP	return period

Details

Growth factors are calculated by the method outlined in Kjeldsen, T (2019), 'The 3-parameter Kappa distribution as an alternative for use with FEH pooling groups.' *Circulation - The Newsletter of the British Hydrological Society*, no. 142

Value

Kappa3 distribution estimated growth factor

Author(s)

Anthony Hammond

Examples

```
#Get a ungauged pooled Lcv and LSkew for catchment 15006
PooledRes <- as.numeric(QuickResults(GetCDs(15006), plot = FALSE)[[2]])
#Calculate Kappa growth factor for the 100-year flood
Kappa3GF(PooledRes[1], PooledRes[2], RP = 100)
```

Kappa3Pars

Kappa3 distribution parameter estimates

Description

Estimated parameters from a sample (using Lmoments) or from user supplied L1 (first L-moment), Lcv (linear coefficient of variation), and LSkew (linear skewness)

Usage

```
Kappa3Pars(x = NULL, L1, LCV, LSKEW)
```

Arguments

x	numeric vector. The sample
L1	first Lmoment
LCV	linear coefficient of variation
LSKEW	linear skewness

Details

The L-moment estimated parameters are by the method detailed in 'Hosking J. Wallis J. 1997 Regional Frequency Analysis: An Approach Based on L-moments. Cambridge University Press, New York'. The Kappa3 distribution is as defined by This is the Kappa3 distribution as defined in Kjeldsen, T (2019), 'The 3-parameter Kappa distribution as an alternative for use with FEH pooling groups.'Circulation - The Newsletter of the British Hydrological Society, no. 142.

Value

Parameter estimates (location, scale, shape)

Author(s)

Anthony Hammond

Examples

```
#Get an annual maximum sample and estimate the parameters.
AM.27090 <- GetAM(27090)
Kappa3Pars(AM.27090$Flow)
#calculate Lmoments and estimate the parameters with L1, L2, Lcv, and Lskew
LPars <- as.numeric(Lmoms(AM.27090$Flow))[c(1,2,5,6)]
Kappa3Pars(L1 = LPars[1], LCV = LPars[2], LSKEW = LPars[3])
```

Lcv *Linear coefficient of variation (Lcv)*

Description

Calculates the Lcv from a sample of data

Usage

Lcv(x)

Arguments

x a numeric vector. The sample of interest

Details

Lcv calculated according to methods outlined by Hosking & Wallis (1997): Regional Frequency Analysis and approach based on LMoments. Also in the Flood Estimation Handbook (1999), volume 3.

Value

Numeric. The Lcv of a sample.

Author(s)

Anthony Hammond

Examples

```
#Get an AMAX sample and calculate the Lmoments
AM.27051 <- GetAM(27051)
Lcv(AM.27051$Flow)
```

LcvUrb *Urban adjustment for the linear coefficient of variation (Lcv)*

Description

Urbanises or de-urbanises the Lcv using the methods outlined in the guidance by Wallingford HydroSolutions: 'WINFAP 4 Urban Adjustment Procedures'

Usage

```
LcvUrb(lcv, URBEXT2000, DeUrb = FALSE)
```

Arguments

lcv	the Lcv (numeric)
URBEXT2000	quantiication of urban and suburbanisation for the subject catchment
DeUrb	logical argument with a default of FALSE. If set to TRUE, de-urbanisation adjustment is performed, if FALSE, urbanisation adjustment is performed

Details

The method for de-urbanisation isn't explicitly provided in 'WINFAP 4 Urban Adjustment Procedures', but the procedure is a re-arrangement of the urbanisation equation, solving for Lcv rather than Lcv-urban.

Value

The urban adjust Lcv or the de-urbanised Lcv

Author(s)

Anthony Hammond

Examples

```
#Choose an urban site (site 53006) from the NRFA data then apply a de-urban
#adjustment using the Lcv and URBEXT2000 displayed
NRFAData[which(rownames(NRFAData) == 53006),]
LcvUrb(0.21, 0.1138, DeUrb = TRUE)
#Get the pooled Lmoment ratios results for catchment 53006 and apply the
#urban adjustment using the pooled Lcv, and the URBEXT2000 for site 53006.
CDs.53006 <- GetCDs(53006)
QuickResults(CDs.53006)[[2]]
LcvUrb(0.196, 0.1138)
```

LKurt

Linear Kurtosis (LKurt)

Description

Calculates the LKurtosis from a sample of data

Usage

```
LKurt(x)
```

Arguments

x a numeric vector. The sample of interest

Details

LKurtosis calculated according to methods outlined by Hosking & Wallis (1997): Regional Frequency Analysis and approach based on LMoments. Also in the Flood Estimation Handbook (1999), volume 3.

Value

Numeric. The LSkew of a sample.

Author(s)

Anthony Hammond

Examples

```
#Get an AMAX sample and calculate the Lmoments
AM.27051 <- GetAM(27051)
LKurt(AM.27051$Flow)
```

Lmoms

Lmoments & Lmoment ratios

Description

Calculates the Lmoments and Lmoment ratios from a sample of data

Usage

```
Lmoms(x)
```

Arguments

x a numeric vector. The sample of interest

Details

Lmoments calculated according to methods outlined by Hosking & Wallis (1997): Regional Frequency Analysis and approach based on LMoments. Also in the Flood Estimation Handbook (1999), volume 3.

Value

A data.frame with one row and column headings; L1, L2, L3, L4, Lcv, LSkew, and LKurt. The first four are the Lmoments and the next three are the Lmoment ratios.

Author(s)

Anthony Hammond

Examples

```
#Get an AMAX sample and calculate the Lmoments
AM.27051 <- GetAM(27051)
Lmoms(AM.27051$Flow)
```

LRatioChange

Adjust L-Ratios in a pooling group

Description

Adjusts the linear coefficient of variation (Lcv) and the linear skewness (LSkew) for a chosen site in a pooling group

Usage

```
LRatioChange(x, SiteID, lcv, lskew)
```

Arguments

x	pooling group derived with the Pool function
SiteID	the identification number of the site in the pooling group that is to be changed (character or integer)
lcv	The user supplied Lcv. numeric
lskew	The user supplied LSkew. numeric

Details

Pooling groups are formed from the NRFAData data.frame and all the Lcv and LSkew values are precalculated using the National River Flow Archive Peak flow dataset noted in the description file. The resulting pooled growth curve is calculated using the Lcv and Lskew in the pooled group. The user may have further data and be able to add further peak flows to the annual maximum samples within a pooling group. If that is the case a new Lcv and Lskew can be determined using the Lmoms function. These new values can be added to the pooling group with this LRatioChange function. Also the permeable adjustment function may have been applied to a site, which provides a new Lcv and LSkew. In which case, the LRatioChange function can be applied. The function creates a new pooling group object and x will still exist in it's original state after the function is applied.

Value

A new pooling group, the same as x except for the user adjusted Lcv and Lskew for the user selected site.

Author(s)

Anthony Hammond

Examples

```
# Get some catchment descriptors and create a pooling group.
CDs.39001 <- GetCDs(39001)
Pool.39001 <- Pool(CDs.39001, iug = TRUE)
# apply the function to create a new adjusted pooling group,
#changing the subject site lcv and lskew to 0.187 and 0.164, respectively
Pool.39001Adj <- LRatioChange(Pool.39001, SiteID = 39001, lcv = 0.187, lskew = 0.164)
```

LSkew	<i>Linear Skewness (LSkew)</i>
-------	--------------------------------

Description

Calculates the LSkew from a sample of data

Usage

```
LSkew(x)
```

Arguments

x a numeric vector. The sample of interest

Details

LSkew calculated according to methods outlined by Hosking & Wallis (1997): Regional Frequency Analysis and approach based on LMoments. Also in the Flood Estimation Handbook (1999), volume 3.

Value

Numeric. The LSkew of a sample.

Author(s)

Anthony Hammond

Examples

```
#Get an AMAX sample and calculate the Lmoments
AM.27051 <- GetAM(27051)
LSkew(AM.27051$Flow)
```

 LSkewUrb

Urban adjustment for the linear skewness (LSkew)

Description

Urbanises or de-urbanises the LSkew using the methods outlined in the guidance by Wallingford HydroSolutions: 'WINFAP 4 Urban Adjustment Procedures'

Usage

```
LSkewUrb(lskew, URBEXT2000, DeUrb = FALSE)
```

Arguments

lskew	the LSkew (numeric)
URBEXT2000	quantification of urban and suburbanisation for the subject site
DeUrb	logical argument with a default of FALSE. If set to TRUE, de-urbanisation adjustment is performed, if FALSE, urbanisation adjustment is performed

Details

The method for de-urbanisation isn't explicitly provided in 'WINFAP 4 Urban Adjustment Procedures', but the procedure is a re-arrangement of the urbanisation equation, solving for LSkew rather than LSkew-urban.

Value

The urban adjust Lcv or the de-urbanised Lcv

Author(s)

Anthony Hammond

Examples

```
#Choose an urban site (site 53006) from the NRFA data then apply a de-urban
#adjustment using the Lcv and URBEXT2000 displayed
NRFAData[which(rownames(NRFAData) == 53006),]
LSkewUrb(0.124, 0.1138, DeUrb = TRUE)
#Get the pooled Lmoment ratios results for catchment 53006 and apply the urban
#Get the CDS & adjustment using the pooled LSkew, and the URBEXT2000 for site 53006.
CDs.53006 <- GetCDs(53006)
QuickResults(CDs.53006)[[2]]
LSkewUrb(0.194, 0.1138)
```

MonthlyStats	<i>Monthly Statistics</i>
--------------	---------------------------

Description

Derives monthly statistics from a data.frame with Dates or POSIXct in the first column and variable of interest in the second

Usage

```
MonthlyStats(
  x,
  stat,
  AggStat = NULL,
  Plot = FALSE,
  ylab = "Magnitude",
  main = "Monthly Statistics",
  col = "grey"
)
```

Arguments

x	a data.frame with Dates or POSIXct in the first column and numeric vector in the second.
stat	the function of interest. mean or sum for example.
AggStat	the aggregating statistic. The default is mean. See details
Plot	logical argument with a default of TRUE. If TRUE the monthly statistics are plotted.
ylab	A label for the y axis of the plot. The default is "Magnitude"
main	A title for the plot. The default is "Monthly Statistics"
col	A choice of colour for the bar plot. A single colour or a vector (a colour for each bar).

Details

The statistic of interest for each month is calculated for each calendar year in the data.frame. An aggregated result is also calculated for each month using an aggregating statistic (the mean by default). The data.frame is first truncated at the first occurrence of January 1st and last occurrence of December 31st.

Value

A list with two elements. The first element is a data.frame with year in the first column and months in the next 12 (i.e. each row has the monthly stats for the year). The second element is a dataframe with month in the first column and the associated aggregated statistic in the second. i.e. the aggregated statistic (default is the mean) for each month is provided.

Author(s)

Anthony Hammond

Examples

```
# Get the mean flows for each month for the Thames at Kingston
QMonThames <- MonthlyStats(ThamesPQ[,c(1,3)], stat = mean,
ylab = "Discharge (m3/s)", main = "Thames at Kingston monthly mean flow")
# Get the monthly sums of rainfall for the Thames at Kingston
PMonThames <- MonthlyStats(ThamesPQ[,c(1,2)], stat = sum,
ylab = "Rainfall (mm)", main = "Thames as Kingston monthly rainfall")
```

NGRDist

British national grid reference (NGR) distances

Description

Calculates the euclidean distance between two british national grid reference points using the pythagorean method

Usage

```
NGRDist(i, j)
```

Arguments

i	a numeric vector of length two. The first being the easting and the second being the northing of the first site
j	a numeric vector of length two. The first being the easting and the second being the northing of the second site

Details

Note, that the result is converted to km when six digits are used for easting and northing, when six digits would usually provide a result in metres.

Value

A distance in kilometres (if six digits for easting and northing are used)

Author(s)

Anthony Hammond

Examples

```
#Calculate the distance between the catchment centroid for the
#Kingston upon Thames river gauge and the catchment centroid for the
#gauge at Ardlethen on the River Ythan. First view the eastings and northings
GetCDs(10001)
GetCDs(39001)
NGRDist(i = c(381355, 839183), j = c(462899, 187850))
```

NonFloodAdj	<i>Non-flood adjustment</i>
-------------	-----------------------------

Description

Adjusts the linear coefficient of variation (Lcv) and the linear skewness to account for non-flood years

Usage

```
NonFloodAdj(x)
```

Arguments

x The annual maximum sample. Numeric vector

Details

The method is the “permeable adjustment method” detailed in chapter 19, volume three of the Flood Estimation Handbook, 1999. The method makes no difference for sites where there are no annual maximums (AM) in the sample that are $< \text{median}(\text{AM})/2$. Once applied the results can be used with the LRatioChange function to update the associated member of a pooling group. There is also the NonFloodAdjPool() function which can be used for multiple sites in a pooling group.

Value

A list is returned. The first element of the list is a dataframe with one row and two columns. Lcv in the first column and Lskew in the second. The second element of the list is another dataframe with one row and three columns. Number of non-flood years in the first column, sample size in the second and the percent of non-flood year in the third.

Author(s)

Anthony Hammond

Examples

```
# Get an annual maximum sample with a BFIHOST above 0.65 and with some
# annual maximums lower than median(AM)/2. And then apply the function.
NonFloodAdj(GetAM(44013)[,2])
```

NonFloodAdjPool *Non-flood adjustment for pooling groups*

Description

Applies the NonFloodAdj function to adjust the LCV and LSKEW of one or more sites in a pooling group.

Usage

```
NonFloodAdjPool(x, Index = NULL, AutoP = NULL, ReturnStats = FALSE)
```

Arguments

x	A pooling group, derived from the Pool() or PoolSmall() functions.
Index	An vector of indices (row numbers) of sites to be adjusted. If Index = NULL (the default) the function is applied to all sites.
AutoP	A percentage (numeric) of non flood years. Any sites in the group exceeding this value will be adjusted. This is an automated approach so that the user doesn't need to specify Index. If no sites are above AutoP, the function is applied to all sites.
ReturnStats	Logical with a default of FALSE. If set to TRUE, a dataframe of non-flood year stats is returned (see 'Value' section below) instead of the adjusted Pooling group.

Details

For more details of the method for individual sites see the details section of the NonFloodAdj function. As a default this function applies NonFloodAdj to every member of the pooling group. Index can be supplied which is the row name/s of the members you wish to adjust. Or AutoP can be applied and is a percentage. Any member with a greater percentage of non-flood years than AutoP is then adjusted.

Value

By default the pooling group is returned with adjusted LCVs and LSKEWs for all sites indexed (or all sites when Index = NULL), or all sites with percentage of non-flood years above AutoP. No difference will be seen for sites with no $AMAX < 0.5QMED$. If ReturnStats is set to TRUE, a dataframe with Non-flood year stats is returned. The dataframe has a row for each site in the pooling group and three columns. The first the number of non-flood years, the second is the number of years, and the third is the associated percentage.

Author(s)

Anthony Hammond

Examples

```
# Set up a pooling group for site 44013. Then apply the function.
Pool44013 <- Pool(GetCDs(44013))
PoolNF <- NonFloodAdjPool(Pool44013)
#return the non flood stats for the pooling group
NonFloodAdjPool(Pool44013, ReturnStats = TRUE)
```

NRFAData	<i>National River Flow Archive descriptors and calculated statistics for sites suitable for pooling</i>
----------	---

Description

A data.frame of catchment descriptors, Lmoments, Lmoment ratios, sample size and median annual maximum flow (QMED). NRFA Peak Flow Dataset - Version 13.0.2.

Usage

```
NRFAData
```

Format

A data frame with 543 rows and 27 variables

Details

The functions for pooling group formation and estimation rely on this dataframe. However, the data frame is open for manipulation in case the user wishes to add sites that aren't included, or change parts where local knowledge has improved on the data. Although, usually, in the latter case, such changes will be more appropriately applied to the formed pooling group. If changes are made, they will only remain within the workspace. If a new workspace is opened and the UKFE package is loaded, the data frame will have returned to it's original state.

Source

<https://nrfa.ceh.ac.uk/peak-flow-dataset>

OptimPars

Optimise distribution parameters

Description

Estimates the parameters of the Generalised extreme value, generalised logistic, Kappa3, or Gumbel distribution from known return period estimates

Usage

```
OptimPars(x, dist = "GenLog")
```

Arguments

x	a data.frame with RPs in the first column and associated estimates in the second column
dist	a choice of distribution for the estimates. The choices are "GenLog", "GEV", "Kappa3", or "Gumbel" - the generalised logistic, generalised extreme value, Kappa3, and Gumbel distribution, respectively. The default is "GenLog"

Details

Given a dataframe with return periods (RPs) in the first column and associated estimates in the second column, this function provides an estimate of the distribution parameters. Ideally the first RP should be 2. Extrapolation outside the RPs used for calibration comes with greater uncertainty.

Value

The parameters of one of four user chosen distributions; Generalised logistic, generalised extreme value, Gumbel, and Kappa3.

Author(s)

Anthony Hammond

Examples

```
#Get some catchment descriptors and some quick results. Then estimate the GenLog parameters
Results <- QuickResults(GetCDs(27051), plot = FALSE)[[1]]
OptimPars(Results[,1:2])
```

 Pool

 Create pooling group

Description

Function to develop a pooling group based on catchment descriptors

Usage

```
Pool(
  CDs = NULL,
  AREA,
  SAAR,
  FARL,
  FPEXT,
  N = 500,
  exclude = NULL,
  iug = FALSE,
  UrbMax = 0.03,
  DeUrb = FALSE
)
```

Arguments

CDs	catchment descriptors derived from either GetCDs or CDsXML
AREA	catchment area in km ²
SAAR	catchment standard average annual rainfall (1961-1990) in mm
FARL	catchment flood attenuation from reservoirs & lakes
FPEXT	catchment floodplain extent. The proportion of the catchment that is estimated to be inundated by a 100-year flood
N	minimum Number of total gauged record years for the pooling group
exclude	sites to exclude from the pooling group. Either a single site reference or a vector of site references (numeric)
iug	iug stands for 'include urban gauge' - which refers to a gauged subject site if it's > UrbMax. It's a logical argument with default of FALSE. TRUE will over-ride the default and add the closest site in catchment descriptor space (should be the gauge of interest) to the pooling group if it has URBEXT2000 >= UrbMax
UrbMax	Maximum URBEXT2000 level with a default of 0.03. Any catchment with URBEXT2000 above this level will be excluded from the pooling group
DeUrb	logical argument with a default of FALSE. If true, the Lcv and LSkew of any site in the pooling group with URBEXT2000 > 0.03 will be de-urbanised

Details

A pooling group is created from a CDs object, derived from GetCDs or CDsXML, or specifically with the catchment descriptors (see arguments). To change the default pooling group, one or more sites can be excluded using the 'exclude' option, which requires either a site reference or multiple site references in a vector. If this is done, the site with the next lowest similarity distance measure is added to the group (until the total number of years is at least N). Sites with URBEXT2000 (urban extent) > 0.03 are excluded by default and this can be adjusted with UrbMax. If a gauged assessment is required and the site of interest is > UrbMax it can be included by setting iug = TRUE. De-urbanise the Lcv and Lskew (L-moment ratios) for sites with URBEXT2000 > UrbMax by setting DeUrb = TRUE. If the user has more data available for a particular site within the pooling group, the Lcv and Lskew for the site can be updated after the group has been finalised. An example of doing so is provided below. The pooling method is outlined in Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation.

Value

A data.frame of the pooling group with site reference row names and 24 columns, each providing catchment & gauge details for the sites in the pooling group.

Author(s)

Anthony Hammond

Examples

```
#Get some catchment descriptors
CDs.73005 <- GetCDs(73005)
#Set up a pooling group object called Pool.73005 excluding sites 79005 & 71011.
#Then print the group to the console
Pool.73005 <- Pool(CDs.73005, exclude = c(79005, 71011))
Pool.73005
#Form a pooling group, called PoolGroup, with the catchment descriptors specifically
PoolGroup <- Pool(AREA = 1000, SAAR = 800, FARL = 1, FPEXT = 0.01)
#Form a pooling group using an urban catchment which is intended for enhanced
#single site estimation - by including it in the group.
CDs.39001 <- GetCDs(39001)
Pool.39001 <- Pool(CDs.39001, iug = TRUE, DeUrb = TRUE)
#Change the Lcv and LSkew of the top site in the pooling group to 0.19 & 0.18,
#respectively.
PoolUpdate <- LRatioChange(Pool.39001, SiteID = 39001, 0.19, 0.18)
```

PoolEst

Pooled flood estimates

Description

Provides pooled results from a pooling group - gauged, ungauged and with urban adjustment if necessary.

Usage

```
PoolEst(
  x,
  gauged = FALSE,
  QMED,
  dist = "GenLog",
  RP = c(2, 5, 10, 20, 50, 75, 100, 200, 500, 1000),
  UrbAdj = FALSE,
  CDs = NULL,
  URBEXT = NULL,
  fseQMED = 1.46
)
```

Arguments

x	pooling group derived from the Pool function
gauged	logical argument with a default of FALSE. TRUE for gauged results and FALSE for ungauged
QMED	estimate of the median annual maximum flow
dist	a choice of distribution for the estimates. The choices are "GenLog", "GEV", "Kappa3", or "Gumbel"; the generalised logistic, generalised extreme value, Kappa3, and Gumbel distribution, respectively. The default is "GenLog"
RP	return period of interest. By default the following RPs are provided: 2, 5, 10, 20, 50, 75, 100, 200, 500, 1000
UrbAdj	logical argument with a default of FALSE. When TRUE, an urban adjustment is applied to the pooled Lcv and LSkew
CDs	catchment descriptors derived from either GetCDs or CDsXML
URBEXT	the catchment URBEXT2000, to be supplied if UrbAdj is TRUE and if CDs have not been
fseQMED	factorial standard error of the median annual maximum (QMED) estimate, used for quantifying ungauged uncertainty. Default is 1.46

Details

PoolEst is a function to provide results from a pooling group derived using the Pool function. QMED (median annual maximum flow) needs to be supplied and can be derived from the QMED function for ungauged estimates or the annual maximum sample for gauged estimates. If the catchment of interest is urban, the UrbAdj argument can be set to TRUE. If this is done, either URBEXT (urban extent) needs to be provided or the catchment descriptors, derived from CDsXML or GetCDs. The methods for estimating pooled growth curves are according to Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation. The methods for estimating the L-moments and growth factors are outlined in the Flood Estimation Handbook (1999), volume 3. The methods for quantifying uncertainty are detailed in Hammond, A. (2022). Easy methods for quantifying the uncertainty of FEH pooling analysis. Circulation - The Newsletter of the British Hydrological Society (152). When UrbAdj = TRUE, urban adjustment is applied to the QMED estimate according to the method outlined in the guidance by Wallingford HydroSolutions: 'WINFAP 4 Urban Adjustment Procedures'.

Value

If RP is default then a list of length 4. Element one is a data frame with columns; return period (a range from 2 - 1000), peak flow estimates (Q), growth factor estimates (GF), lower and upper intervals of uncertainty (68 percent intervals for ungauged and 95 percent for gauged). The second element is the estimated Lcv and Lskew. The third provides distribution parameters for the growth curve. The fourth provides distribution parameters for the frequency curve. If RP is not the default only the first two elements are returned.

Author(s)

Anthony Hammond

Examples

```
#Get some catchment descriptors and form a pooling group. It's urban and
#therefore the site of interest is not included.
CDs.27083 <- GetCDs(27083)
Pool.27083 <- Pool(CDs.27083)
#Get results for the ungauged case, with urban adjustment
PoolEst(Pool.27083, QMED = 12, UrbAdj = TRUE, CDs = CDs.27083)
#Form the group again with the urban gauge included & undertake a gauged estimate
#with urban adjustment. QMED in this example is estimated as the median of the annual
#maximum series for site 27083.
PoolG.27083 <- PoolG.27083 <- Pool(CDs.27083, iug = TRUE, DeUrb = TRUE)
PoolEst(PoolG.27083, QMED = 12.5, UrbAdj = TRUE, CDs = CDs.27083)
```

PoolSmall

Create pooling group for small catchments

Description

Function to develop a small catchments pooling group based on catchment descriptors

Usage

```
PoolSmall(
  CDs = NULL,
  AREA,
  SAAR,
  N = 500,
  exclude = NULL,
  iug = FALSE,
  UrbMax = 0.03,
  DeUrb = FALSE
)
```


Arguments

CDs	catchment descriptors derived from either GetCDs or CDsXML
AREA	catchment area in km2
SAAR	catchment standard average annual rainfall (1961-1990) in mm
N	minimum Number of total gauged record years for the pooling group
exclude	sites to exclude from the pooling group. Either a single site reference or a vector of site references (numeric)
iug	iug stands for 'include urban gauge' - which refers to a gauged subject site if it's > UrbMax. It's a logical argument with default of FALSE. TRUE will over-ride the default and add the closest site in catchment descriptor space (should be the gauge of interest) to the pooling group if it has URBEXT2000 >= UrbMax
UrbMax	Maximum URBEXT2000 level with a default of 0.03. Any catchment with URBEXT2000 above this level will be excluded from the pooling group
DeUrb	logical argument with a default of FALSE. If true, the Lcv and Lskew of any site in the pooling group with URBEXT2000 > 0.03 will be de-urbanised

Details

A pooling group is created from a CDs object, derived from GetCDs or CDsXML, or specifically with the necessary catchment descriptors (see arguments). To change the default pooling group one or more sites can be excluded using the 'exclude' option, which requires either a site reference or multiple site references in a vector. If this is done, the site with the next lowest similarity distance measure is added to the group (until the total number of years is at least N). Sites with URBEXT2000 (urban extent) > 0.03 are excluded by default and this can be adjusted with the UrbMax argument. If a gauged assessment is required and the site of interest is > UrbMax it can be included by setting iug = TRUE. De-urbanise the Lcv and Lskew (L-moment ratios) of sites with URBEXT2000 > 0.03 by setting DeUrb = TRUE. If the user has more data available for a particular site within the pooling group, the Lcv and Lskew for the site can be updated after the group has been finalised.

Value

A data.frame of the pooling group with site reference row names and 24 columns, each providing catchment & gauge details for the sites in the pooling group.

Author(s)

Anthony Hammond

Examples

```
#Get some catchment descriptors
CDs.21001 <- GetCDs(21001)
#Set up a pooling group object called Pool.21001 excluding site 206006
#Then print the group to the console
Pool.21001 <- PoolSmall(CDs.21001, exclude = 206006)
Pool.21001
```

```
#Form a pooling group, called PoolGroup, with the catchment descriptors specifically
PoolGroup <- PoolSmall(AREA = 22, SAAR = 1702)
```

POTextract

Peaks over threshold (POT) data extraction

Description

Extracts independent peaks over a threshold from a sample

Usage

```
POTextract(
  x,
  div = NULL,
  TimeDiv = NULL,
  thresh = 0.975,
  Plot = TRUE,
  ylab = "Magnitude",
  xlab = "Time",
  main = "Peaks over threshold"
)
```

Arguments

x	either a numeric vector or dataframe with date (or POSIXct) in the first column and hydrological variable in the second
div	numeric percentile (between 0 and thresh), either side of which two peaks over the threshold are considered independent. Default is the mean of the sample.
TimeDiv	Number of timesteps to define independence (supplements the div argument). As a default this is NULL and only 'div' defines independence. Currently this is only applicable for data.frames.
thresh	user chosen threshold. Default is 0.975
Plot	logical argument with a default of TRUE. When TRUE, the full hydrograph with the peaks over the threshold highlighted is plotted
ylab	Label for the plot yaxis. Default is "Magnitude"
xlab	Label (character) for the plot x axis. Default is "Time".
main	Title for the plot. Default is "Peaks over threshold"

Details

If the x argument is a numeric vector, the peaks will be extracted with no time information. x can instead be a data.frame with dates in the first column and the numeric vector in the second. In this latter case, the peaks will be time-stamped and a hydrograph, including POT, will be plotted by default. The method of extracting independent peaks assumes that there is a value either side of

which, events can be considered independent. For example, if two peaks above the chosen threshold are separated by the mean flow, they could be considered independent, but not if flow hasn't returned to the mean at any time between the peaks. Mean flow may not always be appropriate, in which case the 'div' argument can be applied (and is a percentile). The TimeDiv argument can also be applied to ensure the peaks are separated by a number of time-steps either side of the peaks. For extracting POT rainfall a div of zero could be used and TimeDiv can be used for further separation - which would be necessary for sub-daily time-series. In which case, with hourly data for example, TimeDiv could be set to 120 to ensure each peak is separated by five days either side as well as at least one hour with 0 rainfall. When plotted, the blue line is the threshold, and the green line is the independence line (div).

Value

Prints the number of peaks per year and returns a data.frame with columns; Date and peak, with the option of a plot. Or a numeric vector of peaks is returned if only a numeric vector of the hydrological variable is input.

Author(s)

Anthony Hammond

Examples

```
#Extract POT data from Thames mean daily flow 2000-10-01 to 2015-09-30 with
#div = mean and threshold = 0.95. Then display the first six rows
ThamesQPOT <- POTextract(ThamesPQ[, c(1,3)], thresh = 0.9)
head(ThamesQPOT)
#Extract Thames POT from only the numeric vector of flows and display the
#first six rows
ThamesQPOT <- POTextract(ThamesPQ[, 3], thresh = 0.9)
head(ThamesQPOT)
#Extract the Thames POT precipitation with a div of 0, the default
#threshold, and 5 timesteps (days) either side of the peak. Then display the first six rows
ThamesPPOT <- POTextract(ThamesPQ[, c(1,2)], div = 0, TimeDiv = 5)
head(ThamesPPOT)
```

POTt

Peaks over threshold (POT) data extraction (quick)

Description

Extracts independent peaks over a threshold from a sample, using time as the independence criteria.

Usage

```
POTt(
  x,
  threshold = 0.975,
  div,
```

```

Plot = TRUE,
PlotType = "l",
main = "Peaks over threhsold",
ylab = "Magnitude",
xlab = "Time"
)

```

Arguments

x	either a numeric vector or dataframe with date (or POSIXct) in the first column and hydrological variable in the second
threshold	user chosen threshold. Default is 0.975
div	number of time steps between peaks to ensure independence.
Plot	logical argument with a default of TRUE. When TRUE, the full hydrograph with the peaks over the threshold highlighted is plotted
PlotType	Type of plot with a default of "l" for line graph. For rainfall type "h" for bars could be used.
main	Title for the plot. Default is "Peaks over threshold"
ylab	Label (character) for the plot y axis. Default is "Magnitude"
xlab	Label (character) for the plot x axis. Default is "Time".

Details

This provides a quicker option than the POTextract function - useful for very long time series'. It only has the option of time division to ensure independence between peaks. If the x argument is a numeric vector, the peaks will be extracted with no time information. x can instead be a data.frame with dates in the first column and the numeric vector in the second. In this latter case, the peaks will be time-stamped and a hydrograph, including POT, will be plotted by default.

Value

A data.frame with columns; Date and peak, with the option of a plot. Or a numeric vector of peaks is returned if only a numeric vector of the variable is input as x.

Author(s)

Anthony Hammond

Examples

```

#Extract POT data from Thames catchment daily rainfall 2000-10-01 to 2015-09-30 with
#div = 14 (14 days) and threshold = 0.975. Then display the first six rows
ThamesPPOT <- POTt(ThamesPQ[, c(1,2)], div = 14)
head(ThamesPPOT)
#Extract Thames rainfall POT from only the numeric vector of rainfall, with threshold
#set to 0.95 and div set to 14. Then display the first six rows
ThamesPPOT <- POTt(ThamesPQ[, 2], threshold = 0.95, div = 14)
head(ThamesPPOT)

```

QMED	<i>QMED (median annual maximum flow) estimate from catchment descriptors</i>
------	--

Description

Estimated median annual maximum flow from catchment descriptors and donor sites

Usage

```
QMED(
  CDs = NULL,
  Don1 = NULL,
  Don2 = NULL,
  UrbAdj = FALSE,
  DonUrbAdj = FALSE,
  AREA,
  SAAR,
  FARL,
  BFIHOST,
  URBEXT2000 = NULL,
  Easting,
  Northing
)
```

Arguments

CDs	catchment descriptors derived from either GetCDs or CDsXML
Don1	numeric site reference for the a single donor (for donor candidates see DonAdj function)
Don2	vector of two site references for two donors (for donor candidates see DonAdj function)
UrbAdj	logical argument with a default of FALSE. True applies an urban adjustment
DonUrbAdj	logical argument with a default of FALSE. If TRUE, an urban adjustment is applied to the donor/s QMEDcde estimate.
AREA	catchment area in km ²
SAAR	standard average annual rainfall (mm)
FARL	flood attenuation from reservoirs and lakes
BFIHOST	baseflow index calculated from the catchment hydrology of soil type classification
URBEXT2000	measure of catchment urbanisation
Easting	Easting. A six digit Easting (British national grid reference).
Northing	Northing. A six digit Northing (British national grid reference).

Details

QMED is estimated from catchment descriptors: $QMED = 8.3062 * AREA^{0.8510} 0.1536^{(1000/SAAR)}$ $FARL^{3.4451} 0.0460^{(BFIHOST^2)}$ as derived in Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation. The single donor method is from the same paper. The method for two donors is outlined in 'Kjeldsen, T. (2019). Adjustment of QMED in ungauged catchments using two donor sites. Circulation - The Newsletter of the British Hydrological Society, 4'. When `UrbAdj = TRUE`, urban adjustment is applied to the QMED estimate according to the method outlined in the guidance by Wallingford HydroSolutions: 'WINFAP 4 Urban Adjustment Procedures'. Urban donors should be avoided, but in the case that the subject catchment is rural, and the donor is urban, the QMEDcd estimate of the donor (or donors) can be urban adjusted by setting the `DonUrbAdj` argument to `TRUE`. For flexibility there is the option to input the relevant catchment descriptors directly rather than a CDs object.

Value

An estimate of QMED from catchment descriptors. If two donors are used the associated weights are also returned

Author(s)

Anthony Hammond

Examples

```
#Get some catchment descriptors and calculate QMED as if it was ungauged, with
#no donors, one donor, and two donors
CDs.55004 <- GetCDs(55004)
QMED(CDs.55004)
QMED(CDs.55004, Don1 = 55012)
QMED(CDs.55004, Don2 = c(55012, 60007))
#Get CDs for urban gauge and calculate QMED with urban adjustment
CDs.27083 <- GetCDs(27083)
QMED(CDs.27083, UrbAdj = TRUE)
```

QMEDData

National River Flow Archive descriptors and calculated statistics for sites suitable for QMED & pooling

Description

A data.frame of catchment & data descriptors relating to the median annual maximum flow (QMED).
NRFA Peak Flow Dataset - Version 13.0.2

Usage

QMEDData

Format

A data frame with 897 rows and 26 variables

Details

The functions for QMED estimation and retrieval of catchment descriptors rely on this dataframe. However, the data frame is open for manipulation in case the user wishes to add sites that aren't included, or change parts where local knowledge has improved on the data. If changes are made, they will only remain within the workspace. If a new workspace is opened and the UKFE package is loaded, the data frame will have returned to its original state.

Source

<https://nrfa.ceh.ac.uk/peak-flow-dataset>

QMEDDonEq

QMED donor adjustment

Description

Applies a donor adjustment to the median annual maximum flow (QMED) estimate

Usage

```
QMEDDonEq(
  AREA,
  SAAR,
  FARL,
  BFIHOST,
  QMEDgObs,
  QMEDgCds,
  xSI,
  ySI,
  xDon,
  yDon,
  alpha = TRUE
)
```

Arguments

AREA	catchment area in km ²
SAAR	standardised average annual rainfall in mm
FARL	flood attenuation from reservoirs and lakes
BFIHOST	the baseflow index as a function of soil type
QMEDgObs	the observed QMED at the donor site

QMEDgCds	the QMED equation derived QMED at the donor site
xSI	the catchment centroid easting for the site of interest
ySI	the catchment centroid northing for the site of interest
xDon	the catchment centroid easting for the donor site
yDon	the catchment centroid northing for the donor site
alpha	a logical argument with a default of TRUE. When FALSE the exponent in the donor equation is set to one. Otherwise it is determined by the distance between the donor and the subject site

Details

Although a single donor adjustment can be applied with the DonAdj() function and the QMED(), this is provided for flexibility. The method is that of Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation (2008).

Author(s)

Anthony Hammond

Examples

```
#Get observed QMED for site 15006
Qob <- median(GetAM(15006)[,2])
#Get QMED equation estimated QMED for the donor site
QCD <- QMED(CDs = GetCDs(15006))
#display CDs for site 27051 & note the easting and northing
GetCDs(27051)
#display CDs for site 15006 & note the easting and northing
GetCDs(15006)
#Apply the QMEDDonEq function with the information gained
QMEDDonEq(194, 1096, 0.955, 0.297, Qob, QCD, xSI = 289289, ySI = 947523, xDon = 280908, yDon = 953653)
```

QMEDfseSS

QMED factorial standard error for gauged sites

Description

Estimates the median annual maximum flow (QMED) factorial standard error (FSE) by bootstrapping the sample

Usage

```
QMEDfseSS(x)
```

Arguments

x a numeric vector. The sample of interest

Details

The bootstrapping procedure resamples from the sample $N \times 500$ times with replacement. After splitting into 500 samples of size N , the median is calculated for each. Then the exponent of the standard deviation of the log transformed residuals is taken as the FSE. i.e. $\exp(\text{sd}(\log(x) - \text{mean}(\log(x))))$, where x is the bootstrapped medians.

Value

The factorial standard error for the median of a sample.

Author(s)

Anthony Hammond

Examples

```
#Extract an AMAX sample and estimate the QMED factorial standard error
AM.203018 <- GetAM(203018)
QMEDfseSS(AM.203018$Flow)
```

QMEDLink

QMED Linking equation

Description

Estimates the median annual maximum flow (QMED) from non-flood flows

Usage

```
QMEDLink(Q5dmf, Q10dmf, DPSBAR, BFI)
```

Arguments

Q5dmf	numeric. The daily mean flow that is exceeded 5 percent of the time
Q10dmf	numeric. The daily mean flow that is exceeded 10 percent of the time
DPSBAR	a catchment descriptor. The average drainage path slope of the catchment
BFI	the baseflow index of the gauged flow

Details

The QMED Linking equation estimates QMED as a function of the flow that is exceeded five percent of the time, the flow that is exceeded 10 percent of the time, the baseflow index, and the catchment descriptor; drainage path slope (DPSBAR). All of these can be found for sites on the National River Flow Archive (NRFA) website. The method is provided in the guidance note 'WINFAP 4 QMED Linking equation' (2016) by Wallingford HydroSolutions.

Author(s)

Anthony Hammond

Examples

```
#Calculate the QMED for site 1001 (Wick at Tarroul)
QMEDLink(10.14, 7.352, 29.90, 0.39)
```

QMEDPOT

Empirical estimate of QMED from peaks over threshold (POT) data

Description

Estimates the median annual maximum flow (QMED) from peaks over threshold data

Usage

```
QMEDPOT(x, ppy)
```

Arguments

x	numerical vector. POT data
ppy	number of peaks per year in the POT data

Details

If there are multiple peaks per year, the peaks per year (ppy) argument is used to convert to the annual scale to derive QMED. If ppy is one, then the median of the POT sample is returned (the median of x).

Author(s)

Anthony Hammond

Examples

```
#Extract some POT data and estimate QMED
ThamesPOT <- POTextract(ThamesPQ[,c(1,3)], thresh = 0.90)
QMEDPOT(ThamesPOT$peak, ppy = 1.867263)
```

QuickResults

*Quick pooled results***Description**

Provides pooled gauged, ungauged, or fake ungauged results, directly from the catchment descriptors

Usage

```
QuickResults(
  CDs,
  gauged = FALSE,
  dons = 2,
  Qmed = NULL,
  FUngauged = FALSE,
  plot = TRUE,
  dist = "GenLog"
)
```

Arguments

CDs	catchment descriptors derived from either GetCDs or CDsXML
gauged	logical argument with a default of FALSE. TRUE for gauged results and FALSE for ungauged
dons	number of donors required with a choice of 0, 1, or 2
Qmed	user supplied QMED which overrides the default QMED estimate
FUngauged	logical argument with a default of FALSE. TRUE provides an ungauged estimate whilst excluding the gauged site (the site with the most similar CDs)
plot	logical argument with a default of TRUE. TRUE provides an extreme value plot. FALSE prevents the plot
dist	a choice of distribution for the estimates. The choices are "GenLog", "GEV", "Kappa3", or "Gumbel; the generalised logistic, generalised extreme value, Kappa3, and Gumbel distributions, respectively. The default is "GenLog"

Details

The quick results function provides results with a default pooling group. If gauged = FALSE the median annual maximum flood (QMED) is estimated from catchment descriptors using the QMED equation and then adjusted with two of the closest un-urban gauged sites (can be changed to 0 or 1 donors). If the site is urban, an urban adjustment is made to the QMED and to the pooled growth curve. If gauged = TRUE QMED is the median of the gauged annual maxima and the growth curve is formed with the gauged weighting procedure (often known as enhanced single site). If the gauged catchment is urban, it's included in the pooling group and deurbanised before an urban adjustment is made to the final growth curve. If FUngauged = TRUE, the top site in the pooling group is

excluded and the estimate is performed henceforth in the manner of `gauged = FALSE`. If the CDs are from a gauged site that is not in the list of sites that are considered suitable for pooling, it won't be included in the pooling group. In which case, if `gauged = TRUE`, the result will be erroneous.

Value

A list of length two. Element one is a data frame with columns; return period (RP), peak flow estimates (Q) and growth factor estimates (GF). Two additional columns quantify the uncertainty. The second element is the estimated Lcv and Lskew (linear coefficient of variation and skewness). By default an extreme value plot is also returned

Author(s)

Anthony Hammond

Examples

```
#Get some catchment descriptors
CDs.73005 <- GetCDs(73005)
#Get default ungauged results
QuickResults(CDs.73005)
#Get gauged results with a GEV distribution
QuickResults(CDs.73005, gauged = TRUE, dist = "GEV")
#Get fake ungauged results with one donor
QuickResults(CDs.73005, FUngauged = TRUE, dons = 1)
```

Rating	<i>Stage-Discharge equation optimisation</i>
--------	--

Description

Optimises a power law rating equation from observed discharge and stage

Usage

```
Rating(x, a = NULL)
```

Arguments

x	a data.frame with discharge in the first column and stage in the second
a	a user defined stage correction

Details

The power law rating equation optimised here has the form $q = c(h+a)^n$; where 'q' is flow, 'h' is the stage, 'c' and 'n' are constants, and 'a' is the stage when flow is zero. The optimisation uses all the data provided in the dataframe (x). If separate rating limbs are necessary, x can be subset per limb. i.e. the rating function would be used multiple times, once for each subset of x. There is the option, with the 'a' argument, to hold the stage correction parameter (a), at a user defined level. If 'a' is NULL it will be calibrated with 'c' & 'n' as part of the optimisation procedure.

Value

A list with three elements. The first is a vector of the three calibrated rating parameters. The second is the rating equation; discharge as a function of stage. The third is the rating equation; stage as a function of discharge. A rating plot is also returned.

Author(s)

Anthony Hammond

Examples

```
# Make up Some data:
Q <- c(177.685, 240.898, 221.954, 205.55, 383.051, 154.061, 216.582)
Stage <- c(1.855, 2.109, 2.037, 1.972, 2.574, 1.748, 2.016)
Observations <- data.frame(Q, Stage)
#apply the rating function:
Rating(Observations)
#Hold the stage correction at zero
Rating(Observations, a = 0)
```

ReFH

Revitalised Flood Hydrograph Model (ReFH)

Description

Provides outputs of the ReFH model from catchment descriptors or user defined inputs

Usage

```
ReFH(
  CDs = NULL,
  Depth = NULL,
  duration = NULL,
  timestep = NULL,
  scaled = NULL,
  PlotTitle = NULL,
  RPa = NULL,
  alpha = TRUE,
  season = NULL,
```

```

AREA = NULL,
TP = NULL,
BR = NULL,
BL = NULL,
Cmax = NULL,
Cini = NULL,
BFinl = NULL,
Rain = NULL
)

```

Arguments

CDs	catchment descriptors derived from either GetCDs or ImportCD
Depth	a numeric value. The depth of rainfall used as input in the estimation of a design hydrograph. The default, when Depth = NULL, is a two year rainfall.
duration	a numeric value. A duration (hrs) for the design rainfall
timestep	a numeric value. A user defined data interval. The default changes depending on the estimated time to peak to formulate a sensible looking result
scaled	a numeric value of peak flow in m3/s
PlotTitle	a character string. A user defined title for the ReFH plot
RPa	return period for alpha adjustment. This is only for the purposes of the alpha adjustment, it doesn't change the rainfall input
alpha	a logical argument with default TRUE. If TRUE the alpha adjustment is applied based on RPa. If FALSE, no alpha adjustment is made
season	a choice of "summer" or "winter". The default is "summer" in urban catchments (URBEXT2000 > 0.03) and "winter" in rural catchments
AREA	numeric. Catchment area in km2.
TP	numeric. Time to peak parameter (hours)
BR	numeric. Baseflow recharge parameter
BL	numeric. Baseflow lag parameter (hours)
Cmax	numeric. Maximum soil moisture capacity parameter (mm)
Cini	numeric. Initial soil moisture content (mm)
BFinl	numeric. Initial baseflow (m3/s)
Rain	numeric. User input rainfall (hourly). A numeric vector

Details

The ReFH is described in the Flood Estimation Handbook Supplementary Report No.1 (2007). The method to derive design rainfall profiles is described in the Flood Estimation Handbook (1999), volume 2. Users can also input their own rainfall with the 'Rain' argument. As a default, when catchment descriptors (CDs) are provided the ReFH function uses catchment descriptors to estimate the parameters of the ReFH model and the two year rainfall for the critical duration. The latter is based on a quadratic interpolation of the catchment descriptors RMED1H, RMED1D, and RMED2D (then a seasonal correction factor is applied). Parameters and initial conditions can also

be individually input by the user. If a parameter argument is used for one or more of the parameters, then these overwrite the CD derived parameters. If a value for the scaled argument is provided (m3/s), a scaled hydrograph is returned. The RPa argument doesn't change the rainfall input and is only needed for the alpha adjustment (see the FEH supplement report no.1).

Value

A list with two elements, and a plot. First element of the list is a data.frame of parameters, initial conditions and the catchment area. The second is a data.frame with columns Rain, NetRain, Runoff, Baseflow, and TotalFlow. If the scale argument is used a numeric vector containing the scaled hydrograph is returned instead of the results dataframe. The plot is of the ReFH output, with rainfall, net-rainfall, baseflow, runoff and total flow. If the scaled argument is used, a scaled hydrograph is plotted.

Author(s)

Anthony Hammond

Examples

```
#Get CDs and apply the ReFH function
CDs.203018 <- GetCDs(203018)
ReFH(CDs.203018)
#Apply the ReFH function, scale to a 100-year flow estimate and change the plot title accordingly
ReFH(CDs.203018, scaled = 182, PlotTitle = "100-Year Design Hydrograph - Site 203018")
#Apply the ReFH function with a user defined initial baseflow
ReFH(CDs.203018, BFinI = 6)
```

SCF

Seasonal correction factor (SCF)

Description

The results of applying the ratio of the seasonal annual maximum rainfall for a given duration to the annual maximum rainfall for the same duration

Usage

```
SCF(SAAR, duration)
```

Arguments

SAAR	standardised average annual rainfall. Numeric
duration	duration in hours. Numeric

Details

The SCF and its use is detailed in R&D Technical Report FD1913/TR - Revitalisation of the FSR/FEH rainfall runoff method (2005). The ReFH model has a design rainfall profile included for winter and summer but the depth duration frequency (DDF) model is calibrated on annual maximum peaks as opposed to seasonal peaks. The SCF is necessary to convert the DDF estimate to a seasonal one. Similarly, the DDF model is calibrated on point rainfall and the area reduction factor converts it to a catchment rainfall for use with a rainfall runoff model such as ReFH (see details of the ReFH function). The final depth, therefore is; $\text{Depth} = \text{DDFdepth} \times \text{ARF} \times \text{SCF}$.

Value

A data.frame of one row and two columns: SCFSummer and SCFWinter.

Author(s)

Anthony Hammond

Examples

```
#Derive the SCFs for a SAAR of 1981 and a duration of 6.5
SCF(1981, 6.5)
```

SimData

Data simulator

Description

Simulation of a random sample from the generalised extreme value, generalised logistic, Gumbel, Kappa3, or generalised Pareto distributions

Usage

```
SimData(n, pars = NULL, dist = "GenLog", GF = NULL)
```

Arguments

n	sample size to be simulated
pars	vector of parameters in the order of location, scale, shape (only location and shape for Gumbel)
dist	choice of distribution. Either "GEV", "GenLog", "Gumbel", "Kappa3", or "Gen-Pareto"
GF	vector of GF inputs in the order of Lcv, LSkew, QMED (only Lcv and QMED if dist = "Gumbel")

Details

The simulated sample can be generated using distribution parameters, or the growth factor (GF) inputs; linear coefficient of variation (Lcv), linear skewness (LSkew) & the median annual maximum (QMED).

Value

A random sample of size n for the chosen distribution.

Author(s)

Anthony Hammond

Examples

```
#Simulate a sample of size 30 using parameters GenLog and parameters 299, 51, -0.042
SimData(30, pars = c(299, 51, -0.042), dist = "GenLog")
#Now simulate using the Lcv, Lskew, and median (0.17, 0.04, 310)
SimData(30, GF = c(0.17, 0.04, 310), dist = "GenLog")
```

ThamesPQ

Kingston upon Thames daily flow and catchment precipitation 2000-10-01 to 2015-09-30

Description

A data.frame of four columns; Date, Precipitation (P), & daily mean flow (Q)

Usage

ThamesPQ

Format

A data frame with 5478 rows and 4 columns:

Date Date

P Precipitation, in mm

Q Daily mean discharge, in m³/s

Source

<https://nrfa.ceh.ac.uk/data/station/meanflow/39001>

TrendTest	<i>Trend hypothesis test</i>
-----------	------------------------------

Description

A hypothesis test for trend

Usage

```
TrendTest(x, method = "mk", alternative = "two.sided")
```

Arguments

x	a numeric vector or a data.frame with dates in the first column and chronologically ordered variable in the second.
method	a choice of test method. Choices are "mk" (Mann Kendall - the default), "pearson", and "spearman".
alternative	the alternative hypothesis. Options are "less", "greater", and "two.sided". The default is "two.sided".

Details

The test can be performed on a numeric vector, or a data.frame with dates in the first column and the associated variable of interest in the second. A choice can be made between Mann Kendall, Pearson, or Spearman tests. The Spearman and Mann Kendall are based on ranks and will therefore have the same results whether dates are included or not. The default is Mann Kendall. The default is to test for any trend (alternative = "two.sided"). For positive trend set alternative to "greater", and to test for negative trend set alternative to "less".

Interpretation: When testing for positive trend (alternative = "greater") the P_value is the probability of exceeding the observed statistic under the null hypothesis (that it is less than zero). The vice versa is true when testing for negative trend (alternative = "less"). For alternative = "two.sided" the P_value is the probability of exceeding the absolute value of the observed statistic under the null hypothesis (that it is different from zero). Low P values indicate that the null hypothesis is less likely.

Value

A data.frame with columns and associated values: P_value, statistic (Kendall's tau, Spearman's rho, or Pearson's correlation coefficient), and a standardised distribution value. The latter is either the z score (for MK test) or students 't' of the observed statistic under the null hypothesis.

Author(s)

Anthony Hammond

Examples

```
#Get AMAX sample and apply a trend test with the default Mann Kendall test.
AM.27083 <- GetAM(27083)
TrendTest(AM.27083)
#Apply the test with the pearson method with dates included and not
TrendTest(AM.27083, method = "pearson")
TrendTest(AM.27083$Flow, method = "pearson")
#Apply the default mk test for positive trend
TrendTest(AM.27083$Flow, alternative = "greater")
```

UAF	<i>Urban adjustment factor (UAF) and percentage runoff urban adjustment factor (PRUAF)</i>
-----	--

Description

UAF and PRUAF from catchment descriptors for QMED estimation in ungauged urban catchments

Usage

```
UAF(CDs = NULL, URBEXT2000, BFIHOST)
```

Arguments

CDs	catchment descriptors derived from either GetCDs or CDsXML
URBEXT2000	quantification of catchment urbanisation (used when CDs is not)
BFIHOST	baseflow index as a function of hydrological soil type of the catchment (used when CDs is not)

Value

a data.frame with columns UAF and PRUAF

Author(s)

Anthony Hammond

Examples

```
#Get some catchment descriptors for an urban catchment calculate the UAF & PRUAF
CDs.53006 <- GetCDs(53006)
UAF(CDs.53006)
#Calculate UAF and PRUAF using a user input URBEXT2000 and BFIHOST
UAF(URBEXT2000 = 0.1138, BFIHOST = 0.3620)
```

UEF

Urban expansion factor

Description

This function provides a coefficient to multiply by URBEXT2000 to adjust it to a given year

Usage

UEF(Year)

Arguments

Year The year for consideration. Numeric

Details

The urban expansion factor is detailed in Bayliss, A. Black, K. Fava-Verde, A. Kjeldsen, T. (2006). URBEXT2000 - A new FEH catchment descriptor: Calculation, dissemination and application. R&D Technical Report FD1919/TR, DEFRA, CEH Wallingford

Value

A numeric urban expansion factor.

Author(s)

Anthony Hammond

Examples

```
# Get an expansion factor for the year 2023
UEF(2023)
```

UKOutline*UK outline*

Description

Easting and northing national grid reference points around the coast of the UK

Usage

UKOutline

Format

A data frame with 3867 rows and 2 variables

X_BNG Easting, British national grid reference

Y_BNG Northing, British national grid reference

Source

<https://environment.data.gov.uk/>

Uncertainty

Uncertainty quantification for gauged and ungauged pooled estimates

Description

Quantification of uncertainty for pooling results for the gauged and ungauged case

Usage

```
Uncertainty(
  x,
  gauged = FALSE,
  RP = 100,
  dist = "GenLog",
  qmed = NULL,
  QMEDfse = 1.46,
  UrbAdj = FALSE,
  CDs = NULL,
  conf = 0.95
)
```

Arguments

x	the pooled group derived from the Pool() function
gauged	a logical argument with a default of FALSE. If FALSE the uncertainty intervals are calculated for the ungauged case. If TRUE they are calculated for the gauged case
RP	the return period of interest. Default is 100
dist	a choice of distribution to use for the estimates. Choices are "GEV", "GenLog" or "Gumbel". The default is "GenLog"
qmed	the QMED estimate for the ungauged case. Or for the gauged if the user wishes to override the median from the NRFA data
QMEDfse	The factorial standard error of the QMED estimate for when an ungauged assessment has been undertaken. The default is 1.46
UrbAdj	applies an urban adjustment to the growth curves

CDs	catchment descriptors derived from either GetCDs or CDsXML. Necessary if a UrbAdj is TRUE
conf	the confidence level of the intervals for the gauged case. Default is 0.95. Must be between 0 and 1

Details

Uncertainty in the ungauged case is calculated as detailed in Hammond, A. (2022). Easy methods for quantifying the uncertainty of FEH pooling analysis. *Circulation - The Newsletter of the British Hydrological Society* (152). The 68 percent and 95 percent intervals are returned. For the gauged case the pooled group is bootstrapped 500 times and the enhanced single site weighted linear skewness (LSkew) and linear coefficient of variation (Lcv) are calculated 500 times accordingly and 500 associated growth factors are calculated. Each growth factor (GF) is multiplied by a randomly selected median annual maximum flow (QMED) from the uncertainty distribution of median estimates for the gauged subject site. The distribution of medians is derived from bootstrapping the gauged site 500 times. The intervals are then the upper and lower quantiles (depending on the conf input) of the distribution of median * GFs. For the gauged case the user can choose the level for the intervals. The default is 0.95. Occasionally the single site central estimate will be outside the uncertainty intervals. In these cases the intervals are widened to incorporate it. i.e. if above the intervals, the upper interval is increased to the single site estimate and vice versa if below. This occurs regardless of the confidence setting. For details about the calculations of weighted growth curves & urban adjustment see the PoolEst() function details. The gauged method is detailed in Hammond, A. (2021). Sampling uncertainty of UK design flood estimation. *Hydrology Research*, 52 (6), 1357–1371.

Value

For the ungauged case a data.frame of four values relating to the lower 68 and upper 68 percent interval and the lower 95 and upper 95 percent intervals. These are headed by the associated percentiles. For the gauged case a numeric vector of two values is provided with the lower and upper intervals of the chosen conf level.

Author(s)

Anthony Hammond

Examples

```
#Get CDs, form an ungauged pooling group and quantify the uncertainty of the
#50-year pooled estimate when using a CDs estimate of QMED with no donors
CDs.203018 <- GetCDs(203018)
Pool.203018 <- Pool(CDs.203018, exclude = 203018)
Uncertainty(Pool.203018, qmed = QMED(CDs.203018), RP = 50)
#Form pooling group with subject site included. Quantify the uncertainty of the
#50-year pooled estimate at the 99% level.
Pool.203018 <- Pool(CDs.203018)
Uncertainty(Pool.203018, gauged = TRUE, RP = 50, conf = 0.99)
```

UncSS

Uncertainty for the single site

Description

Quantifies the aleatoric uncertainty for a single site estimate, by bootstrapping the sample

Usage

```
UncSS(x, func, conf = 0.95, RP = NULL)
```

Arguments

x	a numeric vector. The sample of interest
func	the function to be applied
conf	the confidence level of the intervals
RP	return period. Necessary if func requires RP

Details

The bootstrapping procedure resamples from a sample $N \times 500$ times with replacement. After splitting into 500 samples of size N , the statistic of interest is calculated on each. upper and lower quantiles of the resulting distribution are used as the quantification of uncertainty. Any function that provides an estimate based on a sample of data can be used. Including any function that provides estimates as a function of return period.

Value

A data.frame of three values; central, lower, and upper bootstrapped estimates.

Author(s)

Anthony Hammond

Examples

```
#Extract an AMAX sample and quantify uncertainty for the GEV estimated 50-year flow
AM.203018 <- GetAM(203018)
UncSS(AM.203018$Flow, func = GEVAM, RP = 50)
#Quantify uncertainty for the sample standard deviation at the 90 percent confidence level
UncSS(AM.203018$Flow, func = sd, conf = 0.90)
```

`WeightsGLcv`*Site gauged linear coefficient of variation (Lcv) weightings*

Description

Provides the gauged Lcv weights for each site in a pooling group

Usage

```
WeightsGLcv(x)
```

Arguments

x pooling group derived with the Pool() function

Details

Weighting method as according to Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation

Value

A data.frame with site references in the first column and associated weights in the second

Author(s)

Anthony Hammond

Examples

```
#Get some CDs, form a gauged pooling group, and estimate gauged Lcv
CDs.27051 <- GetCDs(27051)
Pool.27051 <- Pool(CDs.27051)
WeightsGLcv(Pool.27051)
```

`WeightsGLSkew`*Site gauged linear skewness (LSkew) weightings*

Description

Provides the gauged LSkew weights for each site in a pooling group

Usage

```
WeightsGLSkew(x)
```


Arguments

x pooling group derived with the Pool() function

Details

Weighting method as according to Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation

Value

A data.frame with site references in the first column and associated weights in the second

Author(s)

Anthony Hammond

Examples

```
#Get some CDs, form a gauged pooling group, and estimate gauged LSkew
CDs.27051 <- GetCDs(27051)
Pool.27051 <- Pool(CDs.27051)
WeightsGLSkew(Pool.27051)
```

WeightsUnLcv

Site ungauged linear coefficient of variation (Lcv) weightings

Description

Provides the ungauged Lcv weights for each site in a pooling group

Usage

```
WeightsUnLcv(x)
```

Arguments

x pooling group derived with the Pool() function

Details

Weighting method as according to Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation

Value

A data.frame with site references in the first column and associated weights in the second

Author(s)

Anthony Hammond

Examples

```
#Get some CDs, form an ungauged pooling group, and estimate ungauged Lcv
CDs.27051 <- GetCDs(27051)
Pool.27051 <- Pool(CDs.27051, exclude = 27051)
WeightsUnLcv(Pool.27051)
```

WeightsUnLSkew

Site ungauged linear skewness (LSkew) weightings

Description

Provides the ungauged LSkew weights for each site in a pooling group

Usage

```
WeightsUnLSkew(x)
```

Arguments

x pooling group derived with the Pool() function

Details

Weighting method as according to Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation

Value

A data.frame with site references in the first column and associated weights in the second

Author(s)

Anthony Hammond

Examples

```
#Get some CDs, form an ungauged pooling group, and estimate ungauged LSkew
CDs.27051 <- GetCDs(27051)
Pool.27051 <- Pool(CDs.27051, exclude = 27051)
WeightsUnLSkew(Pool.27051)
```

WGaugLcv

Gauged pool weighted linear coefficient of variation (Lcv)

Description

Calculates the gauged weighted Lcv from a pooling group (enhanced single site)

Usage

WGaugLcv(x)

Arguments

x pooling group derived with the Pool() function

Details

Weighting method as according to Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation

Value

the gauged weighted Lcv from a pooling group

Author(s)

Anthony Hammond

Examples

```
#Get some CDs, form a gauged pooling group, and estimate gauged Lcv
CDs.27051 <- GetCDs(27051)
Pool.27051 <- Pool(CDs.27051)
WGaugLcv(Pool.27051)
```

WGaugLSkew

Gauged pool weighted linear skewness (LSkew)

Description

Calculates the gauged weighted LSkew from a pooling group (enhanced single site)

Usage

WGaugLSkew(x)

Arguments

x pooling group derived with the Pool() function

Details

Weighting method as according to Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation

Value

the gauged weighted LSkew from a pooling group

Author(s)

Anthony Hammond

Examples

```
#Get some CDs, form a gauged pooling group, and estimate gauged LSkew
CDs.27051 <- GetCDs(27051)
Pool.27051 <- Pool(CDs.27051)
WGaugLSkew(Pool.27051)
```

WungLcv

Ungauged pool weighted linear coefficient of variation (Lcv)

Description

Calculates the ungauged weighted Lcv from a pooling group

Usage

```
WungLcv(x)
```

Arguments

x pooling group derived with the Pool() function

Details

Weighting method as according to Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation

Value

the ungauged weighted Lcv from a pooling group

Author(s)

Anthony Hammond

Examples

```
#Get some CDs, form an ungauged pooling group, and estimate ungauged Lcv
CDs.27051 <- GetCDs(27051)
Pool.27051 <- Pool(CDs.27051, exclude = 27051)
WungLcv(Pool.27051)
```

WungLSkew

Ungauged pool weighted linear skewness (LSkew)

Description

Calculates the ungauged weighted LSkew from a pooling group

Usage

```
WungLSkew(x)
```

Arguments

x pooling group derived with the Pool() function

Details

Weighting method as according to Science Report: SC050050 - Improving the FEH statistical procedures for flood frequency estimation

Value

the ungauged weighted LSkew from a pooling group

Author(s)

Anthony Hammond

Examples

```
#Get some CDs, form an ungauged pooling group, and estimate ungauged LSkew
CDs.27051 <- GetCDs(27051)
Pool.27051 <- Pool(CDs.27051, exclude = 27051)
WungLSkew(Pool.27051)
```

Zdists

Zdist Goodness of fit measure for pooling groups

Description

Calculates the goodness of fit score for pooling groups.

Usage

Zdists(x)

Arguments

x pooling group derived from the Pool() function

Details

The goodness of fit measure provides a Z-Score which quantifies the number of standard deviations from the mean of a normal distribution. To determine goodness of fit for a given distribution (assume GEV for this example), 500 pooling groups are formed which match the number of sites and samples sizes of the pooling group of interest. These are formed by simulation with the GEV distribution having LCV and LSKEW which are the weighted mean LCV and LSKEW of the pooling group (weighted by sample size) and a median of 1. The weighted mean L-Kurtosis of the observed pooling group (tR4) is compared to the mean and standard deviation (sd) of L-Kurtosis from the simulated pooling groups (tR4_Dist) by calculating the associated Z-score: $(tR4 - \text{mean}(tR4_Dist)) / \text{sd}(tR4_Dist)$. The fit of the distribution can be considered acceptable if the absolute Z-Score is less than 1.645 (essentially a hypothesis test with alpha level equal to 0.1). This is done for all candidate distributions and the lowest absolute score is considered the best fit.

NOTE: This is slightly different from the zdist function described in the science report 'Improving the FEH statistical procedures for flood frequency estimation, Environment Agency (2008)'. That function assumes a theoretical LKurtosis as a function of the pooled LSKEW to compare with a distribution of LKurtosis from simulated pooling groups. This means that the Gumbel distribution cannot be compared (hence the change).

Value

A list with the first element a data.frame of four Z-Scores related to the columns; "GEV", "GenLog", "Gumbel", and "Kappa3". The second element is a character stating which has the best fit.

Author(s)

Anthony Hammond

Examples

```
#Get CDs, form a pooling group and calculate the Zdist  
CDs.203018 <- GetCDs(203018)  
Pool.203018 <- Pool(CDs.203018)  
Zdists(Pool.203018)
```

Index

* datasets

- AMSP, [9](#)
 - NRFAData, [67](#)
 - QMEDData, [78](#)
 - ThamesPQ, [89](#)
 - UKOutline, [92](#)
-
- AddGauge, [4](#)
 - AggDayHour, [5](#)
 - AMextract, [6](#)
 - AMImport, [8](#)
 - AMplot, [8](#)
 - AMSP, [9](#)
 - ARF, [10](#)
-
- BFI, [11](#)
-
- CDsXML, [12](#)
-
- DDF, [13](#)
 - DDF99, [14](#)
 - DDF99Pars, [15](#)
 - DDFImport, [16](#)
 - DesHydro, [17](#)
 - DeTrend, [18](#)
 - DiagPlots, [19](#)
 - DonAdj, [20](#)
-
- EncProb, [21](#)
 - ERPlot, [22](#)
 - EVPlot, [23](#)
 - EVPlotAdd, [24](#)
 - EVPool, [26](#)
-
- GenLogAM, [27](#)
 - GenLogEst, [28](#)
 - GenLogGF, [29](#)
 - GenLogPars, [30](#)
 - GenParetoEst, [31](#)
 - GenParetoGF, [32](#)
 - GenParetoPars, [33](#)
-
- GenParetoPOT, [34](#)
 - GetAM, [35](#)
 - GetCDs, [36](#)
 - GetMetOffice, [36](#)
 - GetNRFA, [37](#)
 - GetQMED, [38](#)
 - GetRainEA, [39](#)
 - GetRainSEPA, [40](#)
 - GEVAM, [41](#)
 - GEVEst, [42](#)
 - GEVGF, [43](#)
 - GEVPars, [44](#)
 - GoFCompare, [45](#)
 - GoFComparePool, [46](#)
 - GumbelAM, [47](#)
 - GumbelEst, [48](#)
 - GumbelGF, [49](#)
 - GumbelPars, [49](#)
-
- H2, [50](#)
 - HydroPlot, [51](#)
-
- Kappa3AM, [53](#)
 - Kappa3Est, [54](#)
 - Kappa3GF, [55](#)
 - Kappa3Pars, [56](#)
-
- Lcv, [57](#)
 - LcvUrb, [57](#)
 - LKurt, [58](#)
 - Lmoms, [59](#)
 - LRatioChange, [60](#)
 - LSkew, [61](#)
 - LSkewUrb, [62](#)
-
- MonthlyStats, [63](#)
-
- NGRDist, [64](#)
 - NonFloodAdj, [65](#)
 - NonFloodAdjPool, [66](#)
 - NRFAData, [67](#)

OptimPars, [68](#)

Pool, [69](#)
PoolEst, [70](#)
PoolSmall, [72](#)
POExtract, [74](#)
POTt, [75](#)

QMED, [77](#)
QMEDData, [78](#)
QMEDDonEq, [79](#)
QMEDfseSS, [80](#)
QMEDLink, [81](#)
QMEDPOT, [82](#)
QuickResults, [83](#)

Rating, [84](#)
ReFH, [85](#)

SCF, [87](#)
SimData, [88](#)

ThamesPQ, [89](#)
TrendTest, [90](#)

UAF, [91](#)
UEF, [92](#)
UKOutline, [92](#)
Uncertainty, [93](#)
UncSS, [95](#)

WeightsGLcv, [96](#)
WeightsGLSkew, [96](#)
WeightsUnLcv, [97](#)
WeightsUnLSkew, [98](#)
WGaugLcv, [99](#)
WGaugLSkew, [99](#)
WungLcv, [100](#)
WungLSkew, [101](#)

Zdists, [102](#)